
DELTALIGHT




FRAX MB 92726 HONEYCOMB DIM5

REFERENCE 26010 9275 N

AVAILABLE IN
FLEMISH BRONZE OUTDOOR 26010 9275 FBRX
ANTHRACITE 26010 9275 N
PINE GREEN 26010 9275 PGR





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.1
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	9 x LENS SP-14° INCL.DIMMABLE LED POWER SUPPLY 900mA-DC INCL.BEAM LENS 26° INCL.HONEYCOMB INCL.1 x CABLE H05 RN-F 5 x 1mm² 2m

Electrical info	
ELECTRICAL	110-277V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 23,4W / CRI>90 (R9: 50) / 2700K / 2423lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	26°
LED TECHNICS (LIGHT SOURCE)	2423lm // 23,4W // 103lm/W
LED TECHNICS (LUMINAIRE)	1357lm // 26,9W // 50lm/W

Requirements

FRAX BRACKET
FRAX PIN
FRAX STRAP

Options

FRAX ANTI VANDAL SCREWS

DELTALIGHT

FRAX MB 92726 HONEYCOMB DIM5

26010 9275 N


Accessories

FRAX M KAP

For detailed installation instructions, please consult the manual : **26010_XX75_HAND.pdf**

FINISH YOUR SPECIFICATION

Pins and plates for bollards




26070 0040 FBRX FRAX PIN FBRX ☐

26070 0040 N FRAX PIN N ☐

26070 0040 PGR FRAX PIN PGR ☐

Fixation components




26070 0060 FBRX FRAX BRACKET FBRX ☐

26070 0060 N FRAX BRACKET N ☐

26070 0060 PGR FRAX BRACKET PGR ☐

Light altering devices




26070 0020 N FRAX M KAP N ☐

DELTALIGHT


FRAX MB 92726 HONEYCOMB DIM5

26010 9275 N

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS ☐



26070 0050 N FRAX STRAP N ☐

Notes: