



D-LINER 19 SBL LOC1 420 930 RD

32031 9300 B

AVAILABLE IN
BLACK 32031 9300 B



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 260mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 0,5m + WIELAND PLUG GST08i2 male green

Electrical info

CLASS	III
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 10W / CRI>90 (R9: 59) / 3000K / 1040lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	1040lm // 10W // 123lm/W
LED TECHNICS (LUMINAIRE)	780lm // 11,5W // 68lm/W

Requirements

LED POWER SUPPLY SET LOC PARALLEL

Options

CONNECTING CABLE LOC PARALLEL



For detailed installation instructions, please consult the manual : [32031_XXX0_HAND.pdf](#)

DELTALIGHT


D-LINER 19 SBL LOC1 420 930 RD


32031 9300 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interlu SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-

FINISH YOUR SPECIFICATION

Emergency units	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current



32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5

Dimtype: DALI

1

Current supply



32010 1200 T CONNECTOR LOC PARALLEL



32010 1310 CONNECTING CABLE LOC PARALLEL 1m



32010 1320 CONNECTING CABLE LOC PARALLEL 2m



32010 1330 CONNECTING CABLE LOC PARALLEL 3m

DELTALIGHT

D-LINER 19 SBL LOCI 420 930 RD

32031 9300 B



32010 1340 CONNECTING CABLE LOC PARALLEL 4m



32010 1350 CONNECTING CABLE LOC PARALLEL 5m

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



32010 0085 LED POWER SUPPLY SET LOC PARALLEL 260mA / 35W DIM5

1


Dimtype: DALI



32010 0105 LED POWER SUPPLY SET LOC PARALLEL 520mA / 35W DIM5

2->2


Dimtype: DALI



32010 0125 LED POWER SUPPLY SET LOC PARALLEL 780mA / 35W DIM5

3->3


Dimtype: DALI



32010 0145 LED POWER SUPPLY SET LOC PARALLEL 1040mA / 35W DIM5

4->4

Dimtype: DALI



32010 0165 LED POWER SUPPLY SET LOC PARALLEL 1300mA / 100W DIM5

5->5

Dimtype: DALI

Notes: