

## SPY 39 TRIMLESS SOFT 93020

24180 9020 GC

AVAILABLE IN

**BLACK** 24180 9020 B

**BRUSHED ALU** 24180 9020 BRA

**BRUSHED ANTHRACITE** 24180 9020 BRAT

**BRUSHED COPPER** 24180 9020 BRCU

**BRUSHED GOLD** 24180 9020 BRG

**BRUSHED OLD BRONZE** 24180 9020 BROB



**FLEMISH BRONZE** 24180 9020 FBR

**FLEMISH GOLD** 24180 9020 FG

**GOLD COLOURED** 24180 9020 GC

**PIANO BLACK** 24180 9020 PB

**WHITE** 24180 9020 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - Ø KIT
<b>RECESSED DEPTH (MM)</b>	80
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	0° to 45° swiveling, 355° rotatable
<b>INFORMATION</b>	REFLECTOR FL-20° EXCL.DIMMABLE LED POWER SUPPLY 350mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	F
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	20°
<b>LED TECHNICS (LIGHT SOURCE)</b>	623lm // 6W // 105lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	508lm // 6,9W // 74lm/W

### Requirements

SPY 39 TUBE  
MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.  
MOUNTING KIT AIR 103  
LED POWER SUPPLY 350mA-DC DIM (Remote)



# DELTALIGHT

## SPY 39 TRIMLESS SOFT 93020

24180 9020 GC

**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30



**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45



**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30




**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

2

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

4(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

3(2)

Dimtype: 1-10V or push button

Cutout dimension (mm): 72



**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

2

Dimtype: 1-10V or DALI or push button

# DELTALIGHT

## SPY 39 TRIMLESS SOFT 93020

24180 9020 GC



**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

2(2)

**Dimtype: DALI**

**Cutout dimension (mm): 72**




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

2(2)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**



**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2)

**Dimtype: DALI**

**Cutout dimension (mm): 55**



**21012 0021** LED POWER SUPPLY MULTI POWER DIM1

3

**Dimtype: 1-10V**

**Cutout dimension (mm): 54**



**21012 0035** LED POWER SUPPLY MULTI POWER DIM5

3

**Dimtype: DALI**

**Cutout dimension (mm): 54**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

4(4)

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 84**



**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

3

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 54**




**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 50**



**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**

# DELTALIGHT

## SPY 39 TRIMLESS SOFT 93020

24180 9020 GC



**21012 0308** LED POWER SUPPLY 350mA / 7,35W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 40**



**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

**Dimtype: DALI**

**Cutout dimension (mm): 30**

### Mounting kits



**15212 2030** MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.

**Cutout dimension (mm): 105**

### Mounting kits stretched ceiling




**15212 0080** MOUNTING KIT SPY 39/52 TRIMLESS CSC



**15212 0160** MOUNTING KIT SPY 39/52 TRIMLESS WSC

### Mounting kits side air + light



**29810 0030** MOUNTING KIT SIDE AIR 103

**Cutout dimension (mm): 168**


# DELTALIGHT

## SPY 39 TRIMLESS SOFT 93020

24180 9020 GC

### Mounting kits top air + light

---




**29810 0230** MOUNTING KIT TOP AIR 103

Cutout dimension (mm): 135

### Mounting kits side air only

---




**29810 0100** MOUNTING KIT SIDE AIR ONLY 1

Cutout dimension (mm): 168

### Mounting kits top air only

---



**29810 0200** MOUNTING KIT TOP AIR ONLY 1

Cutout dimension (mm): 135

### Mounting kits no air

---




**29810 0070** MOUNTING KIT NO AIR 103

Cutout dimension (mm): 168

### Finish your product

---



**24144 0010 B** SPY 39 TUBE B

**24144 0010 FBR** SPY 39 TUBE FBR

**24144 0010 FG** SPY 39 TUBE FG

# DELTALIGHT

## SPY 39 TRIMLESS SOFT 93020

24180 9020 GC

**24144 0010 GC** SPY 39 TUBE GC

**24144 0010 W** SPY 39 TUBE W



**24144 0070** SPY 39 TUBE SBL

Notes: