





POLESANO W 94015

15931 9410 N-B

AVAILABLE IN

ALU GREY-BLACK 15931 9410 A-B

ANTHRACITE-BLACK 15931 9410 N-B



[View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP66
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	5.4
ADJUSTABILITY	0° to 55° swiveling, 355° rotatable
INFORMATION	16 x LENS SP-15° INCLLED POWER SUPPLY 900mA-DC $\lambda > 0,9$ Inrush current : 32A - 355µs @ 230V-AC Max. 10 units on circuit breaker B 16A @ 230V-AC (13 units on B 20A)

Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, ENEC+, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 41,6W / CRI>90 (R9: 62) / 4000K / 5136lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	15°
LED TECHNICS (LIGHT SOURCE)	5136lm // 41,6W // 123lm/W
LED TECHNICS (LUMINAIRE)	4084lm // 47,8W // 85lm/W

Remarks

Take a look at the POLESANO brochure

Options

POLESANO FLOOR BASE

Accessories


HONEYCOMB S105

LINEAR SPREAD LENS S105


For detailed installation instructions, please consult the manual : [15931_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices




431 03 01 B HONEYCOMB S105 B

☐

431 03 02 LINEAR SPREAD LENS S105

☐

Other



15932 0010 N POLESANO FLOOR BASE N

☐

Notes: