



OML50 C - LED ARRAY UP TW 2296mm 950 DIM5

31148 9005



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	@ 2700K: LED cluster 26W / CRI>90 (R9: 50) / 2700K-5000K / 3416lm Or @ 5000K: LED cluster 23,6W / CRI>90 (R9: 50) / 2700K-5000K / 4088lm
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	@ 2700K: 3416lm // 26W // 131lm/W Or @ 5000K: 4088lm // 23,6W // 173lm/W

Opties

WIRELESS CONTROL DIM5

Notes: