DELTALIGHT



ENTERO SQ-L TRIMLESS 92730

REFERENCE 28535 9220 GC

AVAILABLE IN
BLACK 28535 9220 B
FULL WHITE 28535 9220 FW
GOLD COLOURED 28535 9220 GC





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - Ø KIT
RECESSED DEPTH (MM)	165
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 350-1050mA-DC Optional REFLECTORS 18° & 45° available

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,3-36,5W / CRI>90 (R9: 60) / 2700K / 1561-4380lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	4380lm // 36,5W // 120lm/W
LED TECHNICS (LUMINAIRE)	3542lm // 42W // 84lm/W

Remarks

Max.900mA when using 1 accessory; max 800mA when using 2 accessories

Requirements

MOUNTING KIT ENTERO SQUARE L
LED POWER SUPPLY 350 / 500 / 700 / 1050mA-DC DIM (Remote)

Accessories

ENTERO L HONEYCOMB
ENTERO L LINEAR SPREAD LENS
ENTERO L SPREAD LENS
ENTERO L SOFTENING LENS
ENTERO L GLASS SBL

DELTALIGHT

ENTERO SQ-L TRIMLESS 92730

28535 9220 GC

For detailed installation instructions, please consult the manual : **28535_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 **Plasterboard**	28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 **Stucanet**	28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 **Wood**	28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 **Concrete + plaster**	28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 **Lintel + plaster**	28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 **Hollow-core slab + plaster**	28400 0060 - MOUNTING KIT ENTERO SQ-L	Required
 **Stretched ceiling**	28400 0120 - MOUNTING KIT ENTERO SQ-L CSC	Required
	28400 0180 - MOUNTING KIT ENTERO SQ-L WSC	Required

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 2(2) | 2(2) | 2(1) | -

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — 1

Dimtype: 1-10V or DALI or push button

DELTALIGHT

ENTERO SQ-L TRIMLESS 92730

28535 9220 GC



300 90 135 LED POWER SUPPLY MULTI-POWER HV — 1

Dimtype: non-dimmable

Cutout dimension (mm): 90



300 90 136 LED POWER SUPPLY MULTI-POWER HC DIM9 — 1(1)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER — 1

Dimtype: non-dimmable

Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 — 1

Dimtype: 1-10V

Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 — 1

Dimtype: DALI

Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL — 1(1)

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL — 1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 — 1(1)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 — 1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 — 1(0)

Dimtype: non-dimmable

Cutout dimension (mm): 60

ENTERO SQ-L TRIMLESS 92730

28535 9220 GC

Mounting kits



28400 0060 MOUNTING KIT ENTERO SQ-L

Cutout dimension (mm): 142 x 142

Mounting kits stretched ceiling



28400 0120 MOUNTING KIT ENTERO SQ-L CSC



28400 0180 MOUNTING KIT ENTERO SQ-L WSC

Light altering devices



28500 0130 ENTERO L LINEAR SPREAD LENS



28500 0140 ENTERO L SPREAD LENS



28500 0150 ENTERO L SOFTENING LENS



28500 0160 ENTERO L GLASS SBL



28500 0170 B ENTERO L HONEYCOMB SINGLE USE B

DELTALIGHT

ENTERO SQ-L TRIMLESS 92730

28535 9220 GC



28500 0180 B ENTERO L HONEYCOMB DOUBLE USE B

Notes: