





OOONO F PORTABLE 930

29619 9300 B

AVAILABLE IN
BLACK 29619 9300 B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Floor Stand alone
INGRESS PROTECTION	IP20
PROTECTION AGAINST MECHANICAL IMPACT	IK04
WEIGHT (KG)	7.4
ADJUSTABILITY	non adjustable
INFORMATION	INCL.BATTERY PACK 2600mAh INCL.SEPARATE BATTERY CHARGER ON/OFF SWITCH 4h ON FULLY CHARGED BATTERY
Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	III
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	416lm // 9,9W // 42lm/W

Options

INFORM 40 SQ F/T SWARM SENSOR

For detailed installation instructions, please consult the manual : [29619_XXX0_HAND.pdf](#)

DELTALIGHT

OONO F PORTABLE 930

29619 9300 B

Notes: