




EXCLUSIVELY AVAILABLE IN INDIA

COMPO S HP SOFT 93020

REFERENCE 9 15720 9020 B

AVAILABLE IN
BLACK 9 15720 9020 B
CHROMED 9 15720 9020 C
DARK CHROMED 9 15720 9020 DC
WHITE 9 15720 9020 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.164
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,7W / CRI>90 (R9: 50) / 3000K-1800K / 734lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	734lm // 8,7W // 99lm/W
LED TECHNICS (LUMINAIRE)	440lm // 10W // 44lm/W

Requirements	
LED POWER SUPPLY 350 mA - DC	

Accessories	
COMPO S HONEYCOMB SINGLE USE B	
COMPO S LINEAR SPREAD LENS	
COMPO S SPREAD LENS	
COMPO S SOFTENING LENS	
COMPO S GLASS SBL	

For detailed installation instructions, please consult the manual : [9_15720_XXX0_HAND.pdf](#)

DELTALIGHT

COMPO S HP SOFT 93020

9 15720 9020 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 3800	LED POWER SUPPLY MULTIPOWER 10W DIM8 350mA	1
15710 4500	LED POWER SUPPLY MULTIPOWER 12W DIM1 350mA	1
15710 5100	LED POWER SUPPLY MULTIPOWER 8W DALI DT6 350mA	1
Dimtype: DALI		
15710 6100	LED POWER SUPPLY MULTIPOWER 10W DIM8 250mA	1
15710 6200	LED POWER SUPPLY MULTIPOWER 12W DIM1 250mA	1
15710 6300	LED POWER SUPPLY MULTIPOWER 12W DALI DT6 250mA	1

Mounting kits



15710 0010 B MOUNTING KIT COMPO S TRIM B

Cutout dimension (mm): 55

15710 0010 W MOUNTING KIT COMPO S TRIM W

COMPO S HP SOFT 93020

9 15720 9020 B



15710 0040 MOUNTING KIT COMPO S TRIMLESS

☐

Cutout dimension (mm): 55

Light altering devices

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

☐

15710 0110 COMPO S LINEAR SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS

☐

Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL

☐

Cutout dimension (mm): 26,5

Notes: