



OML50 - PRISMATIC LENS DU TW
1640mm 950 DIM5

31649 9005 B

AVAILABLE IN
BLACK 31649 9005 B

 [View on website](#)



General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.1
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 30W / CRI>90 (R9: 50) / 2700K-5000K / 4011lm UP @ 2700K: LED cluster 18,6W / CRI>90 (R9: 50) / 2700K-5000K / 2440lm Or DOWN @ 5000K: LED cluster 27,4W / CRI>90 (R9: 50) / 2700K-5000K / 4781lm UP @ 5000K: LED cluster 16,9W / CRI>90 (R9: 50) / 2700K-5000K / 2920lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 4011lm // 30W // 134lm/W UP @ 2700K: 2440lm // 18,6W // 131lm/W Or DOWN @ 5000K: 4781lm // 27,4W // 174lm/W UP @ 5000K: 2920lm // 16,9W // 173lm/W

Options
WIRELESS CONTROL DIM5

Notes:

DELTALIGHT

OML50 - PRISMATIC LENS DU TW 1640mm 950 DIM5

31649 9005 B