



M26L - SPY 39 FOCUS 930 DIM5

23430 9305 GC

AVAILABLE IN

BLACK 23430 9305 B

BRUSHED ALU 23430 9305 BRA

BRUSHED ANTHRACITE 23430 9305 BRAT

BRUSHED COPPER 23430 9305 BRCU

BRUSHED GOLD 23430 9305 BRG


BRUSHED OLD BRONZE 23430 9305 BROB

FLEMISH BRONZE 23430 9305 FBR

FLEMISH GOLD 23430 9305 FG

GOLD COLOURED 23430 9305 GC

WHITE 23430 9305 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	ADJUSTABLE BEAM 15°-45° EXCLLED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	15°-45°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	303lm // 9,9W // 31lm/W

Requirements



LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23430_XXX5_HAND.pdf](#)




M26L - SPY 39 FOCUS 930 DIM5

23430 9305 GC

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable		10
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable		24
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40		10
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40		20

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
 23358 0000 SLM26L - PROFILE	
 23358 0010 SLM26L - PROFILE 1m	
 23358 0020 SLM26L - PROFILE 2m	

DELTALIGHT

M26L - SPY 39 FOCUS 930 DIM5

23430 9305 GC



23358 0030 SLM26L - PROFILE 3m



Notes: