



OML50 C - LED ARRAY UP TW 2624mm 950 DIM5

31149 9005



[Bekijk op website](#)



| Algemene info | |
|---------------------------------|--|
| LOCATIE | binnen |
| STOF EN WATERDICHTHEID | IP20 |
| GEWICHT (KG) | 1 |
| INFO | INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT |
| Elektrische info | |
| INGANGSSPANNING | 220-240V / 0 50-60Hz |
| KLASSE | I |
| VOEDING | YES |
| DIM TYPE | DALI |
| ENERGIE KLASSE | E |
| CERTIFICATEN | EPD, RCM |
| Info lichtbron | |
| LIGHTSOURCE NAME | LED |
| LICHTBRON | @ 2700K: LED cluster 29,8W / CRI>90 (R9: 50) / 2700K-5000K / 3904lm Or @ 5000K: LED cluster 27W / CRI>90 (R9: 50) / 2700K-5000K / 4672lm |
| SDCM | SDCM3 |
| RISK-GROEP | RG1 |
| LED TECHNIEK (LICHTBRON) | @ 2700K: 3904lm // 29,8W // 131lm/W Or @ 5000K: 4672lm // 27W // 173lm/W |

Opties

WIRELESS CONTROL DIM5

Notes: