



MONTUR L PC LED 930

232 318 93 B

AVAILABLE IN



ALU GREY 232 318 93 A

BLACK 232 318 93 B

FLEMISH BRONZE OUTDOOR 232 318 93 FBRX

ANTHRACITE 232 318 93 N

WHITE 232 318 93 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	3.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.LED POWER SUPPLY 700mA-DC

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,7W / CRI>90 (R9: 50) / 3000K / 2159lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	2159lm // 14,7W // 147lm/W
LED TECHNICS (LUMINAIRE)	1046lm // 16,9W // 62lm/W

For detailed installation instructions, please consult the manual : [232_318_XX_HAND.pdf](#)

Notes:

DELTALIGHT

MONTUR L PC LED 930

232 318 93 B