

ZOOVER



Zoover pretends to be heavy seen its size, nevertheless it looks very lightweight when hung into the room. Designed as a shallow dome, Zoover hides away a circle of light, giving it different looks depending on the point of view. Looking at it from aside, the thermoformed shell has a very neutral appearance. Only when lowering the viewpoint, more and more details catch the eye, as the diffuse light illuminates the inner textures of the scallop. Available in two sizes and two colours for the shade, Zoover adds volume, depth and texture to the room.

Performance	Zoover SBL	Zoover 4CLIP
CRI / TM-30 (3000K):	90 / Rf: 89 / Rg: 97	90
SDCM:	3	1
LED Maintenance:	L70>60,000h	L90>50,000h
*Standard Power:	Down 39.6W Up 5.1W	5.8W
Rating:	Damp	Damp

Delivered Lumens	3000K
Zoover Down SBL:	3842
Zoover Up SBL:	668

Delivered Lumens	2700K		3000K		3500K	
Optic:	MS	MD	MS	MD	MS	MD
Spy 27 S (Style 4CL):		459		480		498
Spy 27 L (Style 4CL):		276		288		299
Spy 39 S (Style 4CL):	614	610	642	638	665	661
Spy 39 L (Style 4CL):	472	509	494	532	511	553

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: ZOVR-140LDU30-B-SBLD14-120PRB-INC

Luminaire	Shape	Size	Fabric Color	Uplight*	CCT	Finish	Style	Controls***	Installation	Hardware Finish ²	Application
ZOV Zoover	R Round	120 Ø1200mm Ø47"-1/4	D Dark Grey L Light Grey	DN Downlight only, no uplight	30 3000K	B Black	4CL ¹ Pendant with 4 Clip Monopoints	D1-120 0-10V dim 120V	PR Round coverplate for 4" junction box PS Square coverplate for 4" junction box	B Black W White	INC Integral Power Supply
		140 Ø1400mm Ø55"-1/8		DU Downlight with uplight added	30 3000K	B Black	SBL Pendant with Inner Illumination 9' Cables 3 suspension points	D1-120 0-10V dim 120V D5-120 Dali dim 120V D14-UNV 0-10V dim 120-277V / FE ELV dim 120V			

¹ See Ordering table on next page for Spot selection associated with Style*CL.

² Applies to PS & PR (coverplate).

*** Contact factory for additional dimming options

Related Products

Soliscape Profile, Spy 52, Spy 66

DELTALIGHT

www.deltalight.com





Ordering

OPTIONAL - ONLY FOR STYLE 4CL

Example: SPY39S1-SP35MDA-GC-B-BV-ZOV-D1-120

Luminaire	Size	Length	Power*	CCT	Optic**	Function	Finish	Inner Finish	Application ²	Controls
SPY Spy Modules	27 27mm/ 1" - 1/16 diameter	S1 Standard L1 ¹ Long	SP Standard Power	27 2700K 30 3000K 35 3500K	MD Medium Spot 30°	A Adjustable	B-B Black-Black FBR-B Flemish Bronze- Black FG-B Flemish Gold-Black GC-B Gold Colored-Black	B Black BV ¹ Black Visor	ZOV Zoover 4CL	D1-120 0-10V dim 120V
	39 39mm/ 1" - 17/32" diameter	S1 Standard L1 ¹ Long	SP Standard Power	27 2700K 30 3000K 35 3500K	MS Medium Narrow Spot 20° MD Medium Spot 30°	A Adjustable	B-B Black-Black FBR-B Flemish Bronze- Black FG-B Flemish Gold-Black GC-B Gold Colored-Black	B Black BV ¹ Black Visor FBR Flemish Bronze FG Flemish Gold GC Gold Colored W White		



¹ Length L1 only available with Inner Finish B.² Zoover luminaire specified separately.

** See page 1 for Delivered Lumens.

Finish Options - Luminaire

ZOOVER 120 SBL


ZOOVER 140 SBL



LIGHT GREY



DARK GREY






UPLIGHT DETAIL


ZOOVER 4CLIP 120

ZOOVER 4CLIP 140

ZOOVER 4CLIP



LIGHT GREY



DARK GREY




DETAIL




Finish Options - Spots



SPY 27 STANDARD SINGLE






LIGHT GREY



BLACK-BLACK

FLEMISH BRONZE-
BLACKFLEMISH GOLD-
BLACKGOLD COLORED-
BLACK


SPY 27 INNER FINISH - LENGTH S ONLY

BLACK
(DEFAULT)BLACK
INSTALLEDVISOR 27
(OPTIONAL)

BLACK VISOR 27

BLACK VISOR 27
INSTALLED


SPY 27 LONG SINGLE WITH BLACK INNER FINISH




BLACK-BLACK

FLEMISH BRONZE-
BLACKFLEMISH GOLD-
BLACKGOLD COLORED-
BLACK


SPY 39 STANDARD SINGLE




BLACK-BLACK

FLEMISH BRONZE-
BLACKFLEMISH GOLD-
BLACKGOLD COLORED-
BLACK

SPY 39 INNER FINISH - LENGTH S ONLY



BLACK




BLACK VISOR 39



FLEMISH BRONZE




FLEMISH GOLD





GOLD COLORED






WHITE

BLACK VISOR 39
INSTALLED

SPY 39 LONG SINGLE




BLACK-BLACK

FLEMISH BRONZE-
BLACKFLEMISH GOLD-
BLACKGOLD COLORED-
BLACK


SPY 39 INNER FINISH - LENGTH L ONLY



BLACK



FLEMISH BRONZE



FLEMISH GOLD




GOLD COLORED




WHITE

Photometric Data


ZOOVER SBL DOWN




ZOOVER SBL DOWN-UP




SPY 27 STANDARD






SPY 27 LONG



SPY 39 STANDARD




SPY 39 LONG




Installation Options

PRB/PRW - COVERPLATE R 121



BLACK -or- WHITE
Requires 4" junction box

PRB/PRW - COVERPLATE S 139



BLACK -or- WHITE
Requires 4" junction box



Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off no
- Power Factor @ Full Load 0.96
- Efficiency @ Full Load ≥ 92
- THD @ Full Load <10% under 120Vac input with 80~100% load condition (for all output currents)

Dimmer Compatibility

- Leviton IP710-LFZ / IP710-DLX
- Lutron DTVT/DVSTV/DVSCSTV/DVSCSTV

D5

- Dimming Control Dali
- Dimming Range 1-100%
- Dim to off no
- Power Factor @ Full Load 0.96
- Efficiency @ Full Load ≥ 92
- THD @ Full Load <10% under 120Vac input with 80~100% load condition (for all output currents)

D14

- Dimming Control Phase Control or 0-10V
- Dimming Range 1-100%
- Dim to off Yes
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥ 90
- THD @ Full Load <20%

Dimmer Compatibility Phase

- Levitation IP1106-1Z / 6631-2
- Lutron DVELV-303P / MAELV-600

Dimmer Compatibility 0-10V

- Levitation IP710-DLZ
- Lutron DTVT-XX

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.