



MINIGRID ON 250 93050 DIM8

100045 9338 W-B



AVAILABLE IN

BLACK-BLACK 100045 9338 B-B

BLACK-WHITE 100045 9338 B-W

WHITE-BLACK 100045 9338 W-B

WHITE-WHITE 100045 9338 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
INFORMATION	2 x REFLECTOR FL-50° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E


Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm)
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
BEAMANGLE	50°
LED TECHNICS (LIGHT SOURCE)	2178lm // 17,2W // 127lm/W
LED TECHNICS (LUMINAIRE)	1753lm // 19,8W // 89lm/W

For detailed installation instructions, please consult the manual : [100045_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



Notes: