




D-LINER 19 SBL LOC1 620 930 RD

32033 9300 B

AVAILABLE IN
BLACK 32033 9300 B



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 390mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 0,5m + WIELAND PLUG GST08i2 male green

Electrical info

CLASS	III
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 15W / CRI>90 (R9: 59) / 3000K / 1500lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	1500lm // 15W // 119lm/W
LED TECHNICS (LUMINAIRE)	1125lm // 17,2W // 65lm/W

Requirements

LED POWER SUPPLY SET LOC PARALLEL

Options

CONNECTING CABLE LOC PARALLEL



For detailed installation instructions, please consult the manual : [32033_XXX0_HAND.pdf](#)

DELTALIGHT


D-LINER 19 SBL LOC1 620 930 RD


32033 9300 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interlu SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-

FINISH YOUR SPECIFICATION

Emergency units	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current



32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5

Dimtype: DALI

1

Current supply



32010 1200 T CONNECTOR LOC PARALLEL



32010 1310 CONNECTING CABLE LOC PARALLEL 1m



32010 1320 CONNECTING CABLE LOC PARALLEL 2m



32010 1330 CONNECTING CABLE LOC PARALLEL 3m

DELTALIGHT

D-LINER 19 SBL LOCI 620 930 RD

32033 9300 B



32010 1340 CONNECTING CABLE LOC PARALLEL 4m



32010 1350 CONNECTING CABLE LOC PARALLEL 5m

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



32010 0095 LED POWER SUPPLY SET LOC PARALLEL 390mA / 35W DIM5

1


Dimtype: DALI



32010 0125 LED POWER SUPPLY SET LOC PARALLEL 780mA / 35W DIM5

2->2


Dimtype: DALI



32010 0155 LED POWER SUPPLY SET LOC PARALLEL 1170mA / 100W DIM5

3->3


Dimtype: DALI



32010 0425 LED POWER SUPPLY SET LOC PARALLEL 1560mA / 100W DIM5

4->4

Dimtype: DALI



32010 0445 LED POWER SUPPLY SET LOC PARALLEL 1950mA / 100W DIM5

5->5

Dimtype: DALI

Notes: