



Image may differ from the actual product
Consult drawing for correct size and structure



INFORM 40 SQ 160 PDS DOWN-UP 93063 DIM5

30722 9335 B-B

DISPONIBLE EN

NOIR-NOIR 30722 9335 B-B

BLANC-NOIR 30722 9335 W-B



[Voir sur le site Web](#)



Informations générales

EMPLACEMENT	interieur
INSTALLATION	Plafond Suspendu
INDICE DE PROTECTION	IP20
POIDS (KG)	2.9
ORIENTATION	non réglable
INFORMATIONS	INCL.PRESENCE & DAYLIGHT SENSOR INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm² 1,6m

Informations électriques

ÉLECTRIQUE	220-240V / 0 50-60Hz
CLASSE	I
ALIMENTATION	YES
TYPE DIM	DALI
CLASSE D'ÉNERGIE	E

Info Source lumineuse

LIGHTSOURCE NAME	LED
SOURCE DE LUMIÈRE	DOWN (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 3000K / 3494lm UP (HO): LED cluster 24,2W / CRI>90 (R9: 50) / 3000K / 3494lm Or DOWN: LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm UP: LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm
VALEURS TM-30	Rf: 92 / Rg: 100 DOWN: rf: 92 / Rg: 100 UP: rf: 92 / Rg: 100
SDCM	SDCM3
GROUPE DE RISQUE	RG1
LM80	L80 > 60000
BEAMANGLE	63°
TECHNIQUES LED (SOURCE LUMINEUSE)	DOWN (HO): 3494lm // 24,2W // 145lm/W UP (HO): 3494lm // 24,2W // 145lm/W Or DOWN: 2534lm // 16,3W // 155lm/W UP: 2534lm // 16,3W // 155lm/W
TECHNIQUES LED (LUMINAIRE)	DOWN (HO): 2417lm // 27,8W // 87lm/W UP (HO): 2301lm // 27,8W // 83lm/W Or DOWN: 1753lm // 18,7W // 94lm/W UP: 1669lm // 18,7W // 89lm/W

INFORM 40 SQ 160 PDS DOWN-UP 93063 DIM5

30722 9335 B-B


Références optionnelles

CABLE BASE R / S



Pour des instructions d'installation détaillées, veuillez consulter le manuel : [30722_XXX5_HAND.pdf](#)

TERMINEZ VOTRE SPÉCIFICATION

le cable d'alimentation

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

divers

	26510 0010 PDS REMOTE CONTROL	☐
	26510 0020 PDS SENSOR PROGRAMMER	☐

DELTALIGHT

INFORM 40 SQ 160 PDS DOWN-UP 93063 DIM5

30722 9335 B-B

Notes: