



## OML50 - PRISMATIC LENS DU TW 1968mm 950 DIM5

31650 9005 B

BESCHIKBAAR IN  
**ZWART** 31650 9005 B



[Bekijk op website](#)



### Algemene info

<b>LOCATIE</b>	binnen
<b>STOF EN WATERDICHTHEID</b>	IP20
<b>GEWICHT (KG)</b>	2.4
<b>INFO</b>	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

### Elektrische info

<b>INGANGSSPANNING</b>	220-240V / 0 50-60Hz
<b>KLASSE</b>	I
<b>VOEDING</b>	YES
<b>DIM TYPE</b>	DALI
<b>ENERGIE KLASSE</b>	E
<b>CERTIFICATEN</b>	EPD, RCM

### Info lichtbron

<b>LIGHTSOURCE NAME</b>	LED
<b>LICHTBRON</b>	DOWN @ 2700K: LED cluster 36W / CRI>90 (R9: 50) / 2700K-5000K / 4813lm UP @ 2700K: LED cluster 22,3W / CRI>90 (R9: 50) / 2700K-5000K / 2928lm Or DOWN @ 5000K: LED cluster 32,9W / CRI>90 (R9: 50) / 2700K-5000K / 5737lm UP @ 5000K: LED cluster 20,3W / CRI>90 (R9: 50) / 2700K-5000K / 3504lm
<b>SDCM</b>	SDCM3
<b>RISK-GROEP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>LED TECHNIEK (LICHTBRON)</b>	DOWN @ 2700K: 4813lm // 36W // 134lm/W UP @ 2700K: 2928lm // 22,3W // 131lm/W Or DOWN @ 5000K: 5737lm // 32,9W // 174lm/W UP @ 5000K: 3504lm // 20,3W // 173lm/W

### Opties

WIRELESS CONTROL DIM5

Notes:

# DELTALIGHT

## **OML50 - PRISMATIC LENS DU TW 1968mm 950 DIM5**

31650 9005 B