





## D-LINER 19 SBL LOC1 620 940 RD

32033 9400 B

AVAILABLE IN  
**BLACK** 32033 9400 B



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	EXCL.LED POWER SUPPLY 390mA-DC INCL.1 x CABLE 2 x 0,75mm <sup>2</sup> - 0,5m + WIELAND PLUG GST08i2 male green

### Electrical info

<b>CLASS</b>	III
<b>ENERGY CLASS</b>	F

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED flex 15W / CRI>90 (R9: 59) / 4000K / 1550lm
<b>SDCM</b>	SDCM3
<b>LM80</b>	L70 > 30000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1550lm // 15W // 123lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1162lm // 17,2W // 67lm/W

### Requirements

LED POWER SUPPLY SET LOC PARALLEL

### Options

CONNECTING CABLE LOC PARALLEL



For detailed installation instructions, please consult the manual : [32033\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT


## D-LINER 19 SBL LOC1 620 940 RD


32033 9400 B

### CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Interlu SAPP	-
 Acoustic climate-control ceiling Hunter Douglas 30BD	-

### FINISH YOUR SPECIFICATION

Emergency units	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current   Max current



**32010 0195** EMERGENCY UNIT 1h LOC PARALLEL DIM5

Dimtype: DALI

1

### Current supply



**32010 1200** T CONNECTOR LOC PARALLEL



**32010 1310** CONNECTING CABLE LOC PARALLEL 1m



**32010 1320** CONNECTING CABLE LOC PARALLEL 2m



**32010 1330** CONNECTING CABLE LOC PARALLEL 3m

# DELTALIGHT

## D-LINER 19 SBL LOCI 620 940 RD

32033 9400 B



**32010 1340** CONNECTING CABLE LOC PARALLEL 4m



**32010 1350** CONNECTING CABLE LOC PARALLEL 5m

### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**32010 0095** LED POWER SUPPLY SET LOC PARALLEL 390mA / 35W DIM5

1


Dimtype: DALI



**32010 0125** LED POWER SUPPLY SET LOC PARALLEL 780mA / 35W DIM5

2->2


Dimtype: DALI



**32010 0155** LED POWER SUPPLY SET LOC PARALLEL 1170mA / 100W DIM5

3->3


Dimtype: DALI



**32010 0425** LED POWER SUPPLY SET LOC PARALLEL 1560mA / 100W DIM5

4->4

Dimtype: DALI



**32010 0445** LED POWER SUPPLY SET LOC PARALLEL 1950mA / 100W DIM5

5->5

Dimtype: DALI

Notes: