

## SPY 39 TRIMLESS 92740

24121 9230 BRCU

AVAILABLE IN

**BLACK** 24121 9230 B

**BRUSHED ALU** 24121 9230 BRA

**BRUSHED ANTHRACITE** 24121 9230 BRAT

**BRUSHED COPPER** 24121 9230 BRCU

**BRUSHED GOLD** 24121 9230 BRG

**BRUSHED OLD BRONZE** 24121 9230 BROB



**FLEMISH BRONZE** 24121 9230 FBR

**FLEMISH GOLD** 24121 9230 FG

**GOLD COLOURED** 24121 9230 GC

**PIANO BLACK** 24121 9230 PB

**WHITE** 24121 9230 W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - Ø KIT
<b>RECESSED DEPTH (MM)</b>	80
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	0° to 45° swiveling, 355° rotatable
<b>INFORMATION</b>	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 350-500mA-DC

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	40°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1041lm // 8,6W // 121lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	844lm // 9,9W // 85lm/W

### Requirements

SPY 39 TUBE or VISOR 39  
MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.  
MOUNTING KIT AIR 103  
LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

# DELTALIGHT

## SPY 39 TRIMLESS 92740

24121 9230 BRCU

For detailed installation instructions, please consult the manual : [24121\\_XXX0\\_HAND.pdf](#)

### CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 <b>System ceiling</b>	 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 <b>Plasterboard</b>	 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 <b>Stucanet</b>	 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 <b>Concrete + plaster</b>	 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 <b>Lintel + plaster</b>	 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 <b>Hollow-core slab + plaster</b>	 15212 2030 - MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.	Required
 <b>Stretched ceiling</b>	 15212 0080 - MOUNTING KIT SPY 39/52 TRIMLESS CSC	Required
	 15212 0160 - MOUNTING KIT SPY 39/52 TRIMLESS WSC	Required
 <b>Ventilation in plasterboard</b>	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
	 29810 0030 - MOUNTING KIT SIDE AIR 103	Required
	 29810 0070 - MOUNTING KIT NO AIR 103	Required
 <b>Ventilation in concrete + plaster</b>	 29810 0070 - MOUNTING KIT NO AIR 103	Required
	 29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required
	 29810 0230 - MOUNTING KIT TOP AIR 103	Required

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

# DELTALIGHT

## SPY 39 TRIMLESS 92740

24121 9230 BRCU



**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30



**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45



**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45




**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30




**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45




**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30



**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6

2 | 2

Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56



**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9

4(4) | 4(4)

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82

# DELTALIGHT

## SPY 39 TRIMLESS 92740

24121 9230 BRCU



**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7

2(2) | 2(1)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 72**



**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

2 | -

**Dimtype: 1-10V or DALI or push button**



**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5

2(2) | 2(1)

**Dimtype: DALI**

**Cutout dimension (mm): 72**



**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6) | 6(4)

**Dimtype: 1-10V or DALI or push button**

**Cutout dimension (mm): 84**



**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

3(2) | 2(1)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**



**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2) | 2(1)

**Dimtype: DALI**

**Cutout dimension (mm): 55**



**300 90 135** LED POWER SUPPLY MULTI-POWER HV

3->4 | 2->4

**Dimtype: non-dimmable**

**Cutout dimension (mm): 90**



**21012 0010** LED POWER SUPPLY MULTI POWER

2 | 2

**Dimtype: non-dimmable**

**Cutout dimension (mm): 50**




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1

3 | 3

**Dimtype: 1-10V**

**Cutout dimension (mm): 54**



**21012 0035** LED POWER SUPPLY MULTI POWER DIM5

3 | 3

**Dimtype: DALI**

**Cutout dimension (mm): 54**

# DELTALIGHT

## SPY 39 TRIMLESS 92740

24121 9230 BRCU



**21012 004W** LED POWER SUPPLY MULTI-POWER WDL

4(4) | 3(3)

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 84**



**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL

3 | 3

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 54**




**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2 | 0

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 50**



**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**



**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->3

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**



**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 | 2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**



**21012 0308** LED POWER SUPPLY 350mA / 7,35W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 40**




**21012 0318** LED POWER SUPPLY 500mA / 10W DIM8

1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 40**




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68

2(2)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**



**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68

2(1)

**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**

# DELTALIGHT

## SPY 39 TRIMLESS 92740

24121 9230 BRCU



**21032 0295**

LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2



Dimtype: DALI

Cutout dimension (mm): 30



**21032 0305**

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5


2



Dimtype: DALI

Cutout dimension (mm): 30

### Mounting kits



**15212 2030** MOUNTING KIT SPY 39/52 TRIMLESS O.F.A.



Cutout dimension (mm): 105

### Mounting kits stretched ceiling




**15212 0080** MOUNTING KIT SPY 39/52 TRIMLESS CSC



**15212 0160** MOUNTING KIT SPY 39/52 TRIMLESS WSC



### Mounting kits side air + light



**29810 0030** MOUNTING KIT SIDE AIR 103



Cutout dimension (mm): 168


# DELTALIGHT

## SPY 39 TRIMLESS 92740

24121 9230 BRCU

### Mounting kits top air + light

---




**29810 0230** MOUNTING KIT TOP AIR 103



Cutout dimension (mm): 135

### Mounting kits side air only

---




**29810 0100** MOUNTING KIT SIDE AIR ONLY 1



Cutout dimension (mm): 168

### Mounting kits top air only

---



**29810 0200** MOUNTING KIT TOP AIR ONLY 1



Cutout dimension (mm): 135

### Mounting kits no air

---




**29810 0070** MOUNTING KIT NO AIR 103



Cutout dimension (mm): 168

### Light altering devices

---



**24144 0030 B** VISOR 39 B




# DELTALIGHT

## SPY 39 TRIMLESS 92740

24121 9230 BRCU

### Finish your product

---



**24144 0010 B** SPY 39 TUBE B

---

**24144 0010 FBR** SPY 39 TUBE FBR

---

**24144 0010 FG** SPY 39 TUBE FG

---

**24144 0010 GC** SPY 39 TUBE GC

---

**24144 0010 W** SPY 39 TUBE W



**24144 0070** SPY 39 TUBE SBL

Notes: