
DELTALIGHT




ENTERO RD-L TW 96545

REFERENCE 28420 9030 B

AVAILABLE IN
BLACK 28420 9030 B
FULL WHITE 28420 9030 FW
GOLD COLOURED 28420 9030 GC





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 112
RECESSED DEPTH (MM)	160
THICKNESS OF MOUNTING SURFACE (MM)	max.16
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.67
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 18° & 30° available

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 2700K-6500K / 2054lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2054lm // 17,8W // 116lm/W
LED TECHNICS (LUMINAIRE)	1617lm // 20W // 79lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW

Options

ENTERO RD-L MOUNTING SET S2

Accessories

ENTERO L HONEYCOMB
ENTERO L LINEAR SPREAD LENS
ENTERO L SPREAD LENS
ENTERO L SOFTENING LENS
ENTERO L GLASS SBL

DELTALIGHT

ENTERO RD-L TW 96545

28420 9030 B

For detailed installation instructions, please consult the manual : **28420_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	-	
 **Plasterboard**	-	
 **Stucanet**	-	
 **Wood**	-	
 **Concrete**	28500 0210 - ENTERO RD-L MOUNTING SET S2	Required
 **Concrete + plaster**	28500 0210 - ENTERO RD-L MOUNTING SET S2	Required
 **Lintel + plaster**	28500 0210 - ENTERO RD-L MOUNTING SET S2	Required
 **Hollow-core slab**	28500 0210 - ENTERO RD-L MOUNTING SET S2	Required
 **Hollow-core slab + plaster**	28500 0210 - ENTERO RD-L MOUNTING SET S2	Required
 **Stretched ceiling**	-	

DELTALIGHT

ENTERO RD-L TW 96545

28420 9030 B


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 — 1

Dimtype: DALI

Cutout dimension (mm): 85


Light altering devices




28500 0130 ENTERO L LINEAR SPREAD LENS




28500 0140 ENTERO L SPREAD LENS




28500 0150 ENTERO L SOFTENING LENS



28500 0160 ENTERO L GLASS SBL



28500 0170 B ENTERO L HONEYCOMB SINGLE USE B




28500 0180 B ENTERO L HONEYCOMB DOUBLE USE B

DELTALIGHT

ENTERO RD-L TW 96545

28420 9030 B

Mounting set S2



28500 0210 ENTERO RD-L MOUNTING SET S2

Notes: