





FRAX SB 930 LINEAR V

26000 9330 FBRX

AVAILABLE IN  
**FLEMISH BRONZE OUTDOOR** 26000 9330 FBRX  
**ANTHRACITE** 26000 9330 N  
**PINE GREEN** 26000 9330 PGR



 [View on website](#)



| General info                         |                                                                                                                                                     |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| LOCATION                             | outdoor                                                                                                                                             |
| INSTALLATION                         | Floor Surface mounted,Wall Surface mounted                                                                                                          |
| INGRESS PROTECTION                   | IP65                                                                                                                                                |
| PROTECTION AGAINST MECHANICAL IMPACT | IK06                                                                                                                                                |
| WEIGHT (KG)                          | 1.3                                                                                                                                                 |
| ADJUSTABILITY                        | 0° to 120° swiveling, 360° rotatable                                                                                                                |
| INFORMATION                          | 4 x LENS SP-14°<br>INCL.LED POWER SUPPLY 700mA-DC<br>INCL.LINEAR SPREAD LENS VERTICAL<br>Oval spread 60°-15°<br>INCL.1 x CABLE H05 RN-F 3 x 1mm² 2m |

| Electrical info |                    |
|-----------------|--------------------|
| ELECTRICAL      | 220-240V / 50-60Hz |
| CLASS           | I                  |
| POWER SUPPLY    | YES                |
| DIM TYPE        | non-dimmable       |
| ENERGY CLASS    | D                  |
| CERTIFICATES    | CB, ENEC, EPD, RCM |

| Lightsource info            |                                                  |
|-----------------------------|--------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                              |
| LIGHTSOURCE                 | LED cluster 8W / CRI>90 (R9: 60) / 3000K / 961lm |
| TM-30 VALUES                | Rf: 92 / Rg: 99                                  |
| SDCM                        | SDCM3                                            |
| RISKGROUP                   | RG2                                              |
| LM80                        | L80 > 150000                                     |
| BEAMANGLE                   | 14°                                              |
| LED TECHNICS (LIGHT SOURCE) | 961lm // 8W // 120lm/W                           |
| LED TECHNICS (LUMINAIRE)    | 673lm // 9,2W // 73lm/W                          |

| Requirements |  |
|--------------|--|
| FRAX BRACKET |  |
| FRAX PIN     |  |
| FRAX STRAP   |  |

| Options                 |  |
|-------------------------|--|
| FRAX ANTI VANDAL SCREWS |  |

| Accessories |  |
|-------------|--|
| FRAX S KAP  |  |

For detailed installation instructions, please consult the manual : [26000\\_XXX0\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Pins and plates for bollards

|                                                                                   |                                      |                          |
|-----------------------------------------------------------------------------------|--------------------------------------|--------------------------|
|  | <b>26070 0040 FBRX</b> FRAX PIN FBRX | <input type="checkbox"/> |
|                                                                                   | <b>26070 0040 N</b> FRAX PIN N       | <input type="checkbox"/> |
|                                                                                   | <b>26070 0040 PGR</b> FRAX PIN PGR   | <input type="checkbox"/> |

Fixation components

|                                                                                     |                                          |                          |
|-------------------------------------------------------------------------------------|------------------------------------------|--------------------------|
|  | <b>26070 0060 FBRX</b> FRAX BRACKET FBRX | <input type="checkbox"/> |
|                                                                                     | <b>26070 0060 N</b> FRAX BRACKET N       | <input type="checkbox"/> |
|                                                                                     | <b>26070 0060 PGR</b> FRAX BRACKET PGR   | <input type="checkbox"/> |

Light altering devices

|                                                                                    |                                  |                          |
|------------------------------------------------------------------------------------|----------------------------------|--------------------------|
|  | <b>26070 0010 N</b> FRAX S KAP N | <input type="checkbox"/> |
|------------------------------------------------------------------------------------|----------------------------------|--------------------------|

# DELTALIGHT

## FRAX SB 930 LINEAR V

26000 9330 FBRX

### Other



**26070 0030** FRAX ANTI VANDAL SCREWS 5 PCS

☐

**26070 0050 N** FRAX STRAP N

☐

Notes: