





SPY 52 WALLWASH 930 ADM SLIM DIM5

19886 9305 B

AVAILABLE IN

BLACK 19886 9305 B

WHITE 19886 9305 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	WALLWASH LENS 3F MULTI DIMMABLE POWER SLIM ADAPTER 350-500mA Current selection via jumper on adapter

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 500mA: LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm Or @ 350mA: LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	@ 500mA: rf: 90 / Rg: 99 @ 350mA: rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	@ 500mA: 1089lm // 8,6W // 127lm/W Or @ 350mA: 787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	@ 500mA: 514lm // 9,9W // 52lm/W Or @ 350mA: 371lm // 6,7W // 56lm/W

Requirements

TRACK 3F DIM

For detailed installation instructions, please consult the manual : [19886_XXX5_HAND.pdf](#)

DELTALIGHT

SPY 52 WALLWASH 930 ADM SLIM DIM5

19886 9305 B

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
<u>200 14 410</u>	TRACK 3F DIM H 1m	1000 m 1.6 kg	 
<u>200 14 420</u>	TRACK 3F DIM H 2m	2000 m 3.2 kg	 
<u>200 14 430</u>	TRACK 3F DIM H 3m	3000 m 4.8 kg	 
TRACK 3F DIM IN			Available Colours
<u>200 13 410</u>	TRACK 3F DIM IN 1m	1000 m 1.2 kg	 
<u>200 13 420</u>	TRACK 3F DIM IN 2m	2000 m 2.4 kg	 
<u>200 13 430</u>	TRACK 3F DIM IN 3m	3000 m 3.5 kg	 
TRACK 3F DIM ON			Available Colours
<u>200 12 410</u>	TRACK 3F DIM ON 1m	1000 m 1.1 kg	  
<u>200 12 420</u>	TRACK 3F DIM ON 2m	2000 m 2.1 kg	  
<u>200 12 430</u>	TRACK 3F DIM ON 3m	3000 m 3.1 kg	  

Notes: