DELTALIGHT



OML50 - PRISMATIC LENS DU TW 2296mm 950 DIM5

REFERENCE 31651 9005 B

AVAILABLE IN
BLACK 31651 9005 B

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.7
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 42W / CRI>90 (R9: 50) / 2700K-5000K / 5615lm UP @ 2700K: LED cluster 26W / CRI>90 (R9: 50) / 2700K-5000K / 3416lm Or DOWN @ 5000K: LED cluster 38,4W / CRI>90 (R9: 50) / 2700K-5000K / 6693lm UP @ 5000K: LED cluster 23,6W / CRI>90 (R9: 50) / 2700K-5000K / 4088lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 5615lm // 42W // 134lm/W UP @ 2700K: 3416lm // 26W // 131lm/W Or DOWN @ 5000K: 6693lm // 38,4W // 174lm/W UP @ 5000K: 4088lm // 23,6W // 173lm/W

Options

WIRELESS CONTROL DIM5

Notes:

OML50 - PRISMATIC LENS DU TW 2296mm 950 DIM5

31651 9005 B