



MONTUR MINI M 930

232 012 93 W

AVAILABLE IN



ALU GREY 232 012 93 A

BLACK 232 012 93 B

FLEMISH BRONZE OUTDOOR 232 012 93 FBRX

ANTHRACITE 232 012 93 N

WHITE 232 012 93 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS OPAL INCL.LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, LCA, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 4,2W / CRI>90 (R9: 50) / 3000K / 617lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	617lm // 4,2W // 147lm/W
LED TECHNICS (LUMINAIRE)	253lm // 4,8W // 52lm/W

For detailed installation instructions, please consult the manual : [232_012_XX_HAND.pdf](#)

DELTALIGHT

MONTUR MINI M 930

232 012 93 W

Notes: