DELTALIGHT

HALOSCAN ON 2 MP SOFT 93014 DIM8

REFERENCE 23150 9018 W-W

AVAILABLE IN
BLACK-BLACK 23150 9018 B-B
BLACK-GOLD COLORED 23150 9018 B-GC
WHITE-WHITE 23150 9018 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS SP-14° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm)
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	1246lm // 12W // 105lm/W
LED TECHNICS (LUMINAIRE)	1064lm // 14W // 77lm/W

Accessories

HALOSCAN HONEYCOMB
HALOSCAN LINEAR SPREAD LENS
HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : **23150_XXX8_HAND.pdf**

DELTALIGHT

HALOSCAN ON 2 MP SOFT 93014 DIM8

23150 9018 W-W

FINISH YOUR SPECIFICATION

Light altering devices



23110 0040 HALOSCAN LINEAR SPREAD LENS ☐



23110 0050 B HALOSCAN HONEYCOMB B ☐



23110 0060 B HALOSCAN KAP MP B ☐

23110 0060 W HALOSCAN KAP MP W ☐

Notes: