

INLET TRIMLESS XS 927



13211 9200 W-W

AVAILABLE IN

BLACK-WHITE 13211 9200 B-W

GOLD COLORED-WHITE 13211 9200 GC-W

WHITE-WHITE 13211 9200 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	50
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 180mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 0,5W / CRI>90 (R9: 55) / 2700K / 64lm
TM-30 VALUES	rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	64lm // 0,5W // 130lm/W
LED TECHNICS (LUMINAIRE)	15lm // 0,6W // 26lm/W

Requirements

MOUNTING KIT INLET TRIMLESS XS
LED POWER SUPPLY 180mA-DC (Remote)

For detailed installation instructions, please consult the manual : [13211_XXX0_HAND.pdf](#)

DELTALIGHT

INLET TRIMLESS XS 927

13211 9200 W-W

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21012 0080 LED POWER SUPPLY MULTI POWER 60-360mA-DC

15(14)

Dimtype: non-dimmable

Cutout dimension (mm): 40

Mounting kits



13210 0010 MOUNTING KIT INLET TRIMLESS XS

Cutout dimension (mm): 30 x 135

Notes: