



OML50 - PRISMATIC LENS DU TW 2624mm 950 DIM5

31652 9005 B

BESCHIKBAAR IN
ZWART 31652 9005 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	3.1
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN @ 2700K: LED cluster 48W / CRI>90 (R9: 50) / 2700K-5000K / 6418lm UP @ 2700K: LED cluster 29,8W / CRI>90 (R9: 50) / 2700K-5000K / 3904lm Or DOWN @ 5000K: LED cluster 43,9W / CRI>90 (R9: 50) / 2700K-5000K / 7650lm UP @ 5000K: LED cluster 27W / CRI>90 (R9: 50) / 2700K-5000K / 4672lm
SDCM	SDCM3
RISK-GROEP	RG1
LED TECHNIEK (LICHTBRON)	DOWN @ 2700K: 6418lm // 48W // 134lm/W UP @ 2700K: 3904lm // 29,8W // 131lm/W Or DOWN @ 5000K: 7650lm // 43,9W // 174lm/W UP @ 5000K: 4672lm // 27W // 173lm/W

Opties

WIRELESS CONTROL DIM5

Notes:

DELTALIGHT

OML50 - PRISMATIC LENS DU TW 2624mm 950 DIM5

31652 9005 B