



MULTINOVA 30 DOWN-UP TW 930 DIM5



27920 9005 GC

AVAILABLE IN

BLACK 27920 9005 B

GOLD COLOURED 27920 9005 GC

WHITE 27920 9005 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY - DALI (DT8)
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 8,8W / CRI>90 (R9: 63) / 2700K-6500K / 1262lm UP @ 2700K: LED cluster 2,7W / CRI>90 (R9: 63) / 2700K-6500K / 379lm Or DOWN @ 6500K: LED cluster 8,9W / CRI>90 (R9: 81) / 2700K-6500K / 1352lm UP @ 6500K: LED cluster 2,7W / CRI>90 (R9: 81) / 2700K-6500K / 406lm
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 1262lm // 8,8W // 143lm/W UP @ 2700K: 379lm // 2,7W // 143lm/W Or DOWN @ 6500K: 1352lm // 8,9W // 153lm/W UP @ 6500K: 406lm // 2,7W // 153lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2700K: 936lm // 10,1W // 93lm/W UP @ 2700K: 358lm // 3,1W // 115lm/W Or DOWN @ 6500K: 1006lm // 10,2W // 98lm/W UP @ 6500K: 383lm // 3,1W // 123lm/W
Options	
MULTINOVA 30 SUSPENSION SET	

DELTALIGHT


MULTINOVA 30 DOWN-UP TW 930 DIM5

27920 9005 GC

For detailed installation instructions, please consult the manual : [27920_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Suspension parts



27910 0020 B MULTINOVA 30 SUSPENSION SET 5x0,75 3m B

☐

27910 0020 W MULTINOVA 30 SUSPENSION SET 5x0,75 3m W

☐

Notes: