
DELTALIGHT




# LOGIC 190 R LINEAR 927 DIM5

**REFERENCE** 30213 9205 INOX

AVAILABLE IN
**INOX** 30213 9205 INOX




View on website

| General info | |
|---|---|
| **LOCATION** | outdoor |
| **INSTALLATION** | Floor Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | round - BOX |
| **RECESSED DEPTH (MM)** | 190 |
| **INGRESS PROTECTION** | IP67 |
| **PROTECTION AGAINST MECHANICAL IMPACT** | IK10 |
| **WEIGHT (KG)** | 2 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | 9 x LENS SP-14°<br>INCL.DIMMABLE LED POWER SUPPLY 500mA-DC<br>INCL.LINEAR SPREAD LENS<br>Oval spread 60°-15°<br>INCL.1 x CABLE H07 RN-F 5 x 1mm² 0,5m<br>INCL.IP68 CONNECTOR 5P<br>ESG 10mm max.500kg |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 110-240V / 50-60Hz |
| **CLASS** | I |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | F |
| **CERTIFICATES** | CB, ENEC, EPD, RCM |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 12,6W / CRI>90 (R9: 50) / 2700K / 1466lm |
| **TM-30 VALUES** | Rf: 91 / Rg: 100 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG2 |
| **LM80** | L80 > 150000 |
| **BEAMANGLE** | 14° |
| **LED TECHNICS (LIGHT SOURCE)** | 1466lm // 12,6W // 116lm/W |
| **LED TECHNICS (LUMINAIRE)** | 957lm // 14W // 66lm/W |

**Requirements**

LOGIC 190 R BOX

**Options**

LOGIC 190 ANTI VANDAL SCREWS 2 PCS

DELTALIGHT


# LOGIC 190 R LINEAR 927 DIM5

30213 9205 INOX

For detailed installation instructions, please consult the manual : **30213_XXX5_HAND.pdf**

## FINISH YOUR SPECIFICATION


### Ground mounting boxes




**30210 0010** LOGIC 190 R BOX ☐


**Cutout dimension (mm): 300 x 230**

### Waterproof connection parts




**21034 0150** IP68 Y-CONNECTOR 5P ☐

### Other



**30210 0020** LOGIC 190 ANTI VANDAL SCREWS 2 PCS ☐

Notes: