
DELTALIGHT




COMPO M SOFT 93020

REFERENCE 9 15728 9020 C

AVAILABLE IN
BLACK 9 15728 9020 B
CHROMED 9 15728 9020 C
DARK CHROMED 9 15728 9020 DC
WHITE 9 15728 9020 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 110
RECESSED DEPTH (MM)	105
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.258
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,8W / CRI>90 (R9: 50) / 3000K-1800K / 1307lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1307lm // 11,8W // 110lm/W
LED TECHNICS (LUMINAIRE)	860lm // 14W // 63lm/W

Requirements

LED POWER SUPPLY 350 mA - DC

Accessories

COMPO M HONEYCOMB SINGLE USE B
COMPO M LINEAR SPREAD LENS
COMPO M SPREAD LENS
COMPO M SOFTENING LENS
COMPO M GLASS SBL

For detailed installation instructions, please consult the manual : **9_15728_XXX0_HAND.pdf**

DELTALIGHT

COMPO M SOFT 93020

9 15728 9020 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
 Plasterboard	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
 Wood	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures


of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 4100	LED POWER SUPPLY MULTIPOWER 12W DIM8 350mA	1
15710 4500	LED POWER SUPPLY MULTIPOWER 12W DIM1 350mA	1
15710 5300	LED POWER SUPPLY MULTIPOWER 12W DALI DT6 350mA	1

Dimtype: DALI

Mounting kits



15710 0020 B MOUNTING KIT COMPO M TRIM B

Cutout dimension (mm): 76

15710 0020 W MOUNTING KIT COMPO M TRIM W



15710 0050 MOUNTING KIT COMPO M TRIMLESS

Cutout dimension (mm): 76

DELTALIGHT

COMPO M SOFT 93020

9 15728 9020 C

Light altering devices

15710 1100 B COMPO M HONEYCOMB SINGLE USE B ☐

15710 1110 COMPO M LINEAR SPREAD LENS ☐

Cutout dimension (mm): 32,5

15710 1120 COMPO M SPREAD LENS ☐

Cutout dimension (mm): 32,5

15710 1130 COMPO M SOFTENING LENS ☐

Cutout dimension (mm): 32,5

15710 1140 COMPO M GLASS SBL ☐

Cutout dimension (mm): 32,5

Notes: