



OCTAV 27 CLIP 92730

29011 9220 W-W

AVAILABLE IN



BLACK-BLACK 29011 9220 B-B

FLEMISH BRONZE-BLACK 29011 9220 FBR-B

FLEMISH GOLD-BLACK 29011 9220 FG-B

GOLD COLORED-BLACK 29011 9220 GC-B

WHITE-WHITE 29011 9220 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Semi-recessed
CUTOUT SHAPE/SIZE (MM)	round - 43
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 350mA-DC SPY 27 L TUBE B included

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	276lm // 6,7W // 41lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

For detailed installation instructions, please consult the manual : [29011_XXX0_HAND.pdf](#)

DELTALIGHT

OCTAV 27 CLIP 92730

29011 9220 W-W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Concrete	-
 Hollow-core slab	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

2

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45




300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL











2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

OCTAV 27 CLIP 92730










29011 9220 W-W

	300 90 61	LED POWER SUPPLY MULTI-POWER DIM6	2	☐
Dimtype: mains (phase cut-off) or push button				
Cutout dimension (mm): 56				
	300 90 63	LED POWER SUPPLY MULTI-POWER DIM9	4(4)	☐
Dimtype: 1-10V or DALI or push button				
Cutout dimension (mm): 82				
	300 90 64	LED POWER SUPPLY MULTI-POWER DIM7	2(2)	☐
Dimtype: 1-10V or push button				
Cutout dimension (mm): 72				
	300 90 67	LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	2	☐
Dimtype: 1-10V or DALI or push button				
	300 90 68	LED POWER SUPPLY MULTI-POWER DIM5	2(2)	☐
Dimtype: DALI				
Cutout dimension (mm): 72				
	300 90 69	LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6)	☐
Dimtype: 1-10V or DALI or push button				
Cutout dimension (mm): 84				
	300 90 124	LED POWER SUPPLY MULTI-POWER DIM7	3(2)	☐
Dimtype: 1-10V or push button				
Cutout dimension (mm): 55				
	300 90 125	LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2)	☐
Dimtype: DALI				
Cutout dimension (mm): 55				
	300 90 135	LED POWER SUPPLY MULTI-POWER HV	3->4	☐
Dimtype: non-dimmable				
Cutout dimension (mm): 90				
	21012 0010	LED POWER SUPPLY MULTI POWER	2	☐
Dimtype: non-dimmable				
Cutout dimension (mm): 50				

DELTALIGHT

OCTAV 27 CLIP 92730

29011 9220 W-W

	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	3	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	3	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	4(4)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	3	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	2->2 0	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	2	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 40	1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	2(2)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2	☐

DELTALIGHT

OCTAV 27 CLIP 92730

29011 9220 W-W

Notes: