



MINIGRID IN TRIMLESS 2 HP 92720

100050 9210 W-B



AVAILABLE IN

BLACK-BLACK 100050 9210 B-B

BLACK-WHITE 100050 9210 B-W

WHITE-BLACK 100050 9210 W-B

WHITE-WHITE 100050 9210 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	160
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	0° to 25° swiveling, 355° rotatable
INFORMATION	2 x REFLECTOR SP-20° EXCL.LED POWER SUPPLY 500-700mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 16,3-23,2W / CRI>90 (R9: 60) / 2700K / 2209-3031lm)
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	6062lm // 46,4W // 130lm/W
LED TECHNICS (LUMINAIRE)	4272lm // 53,4W // 80lm/W

Requirements

MINIGRID IN 2 MOUNTING KIT HP
LED POWER SUPPLY 500 / 700mA-DC DIM (Remote)

Accessories

HONEYCOMB 72
SOFTENING LENS 72

For detailed installation instructions, please consult the manual : [100050_XXX0_HAND.pdf](#)

DELTALIGHT

MINIGRID IN TRIMLESS 2 HP 92720

100050 9210 W-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 202 71 95 02 HP - MINIGRID IN 2 MOUNTING KIT HP	Required
 Plasterboard	 202 71 95 02 HP - MINIGRID IN 2 MOUNTING KIT HP	Required
 Stucanet	 202 71 95 02 HP - MINIGRID IN 2 MOUNTING KIT HP	Required

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

1/2

Dimtype: 1-10V

Cutout dimension (mm): 30




300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1/2

Dimtype: DALI

Cutout dimension (mm): 45




300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

1/2

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

1/2

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 48 700 ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1




1/2

Dimtype: 1-10V

Cutout dimension (mm): 30





MINIGRID IN TRIMLESS 2 HP 92720

100050 9210 W-B

	300 48 700 ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	1/2	☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		
	300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL	1/2	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 30		
	300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL	1/2	☐
	Dimtype: WDL = wireless dimmable		
	Cutout dimension (mm): 45		
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6	1/2 1/2	☐
	Dimtype: mains (phase cut-off) or push button		
	Cutout dimension (mm): 56		
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1(1) 1(1/2)	☐
	Dimtype: 1-10V or DALI or push button		
	Cutout dimension (mm): 82		
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	1/2->1/2(0) 1/2->1/2(0)	☐
	Dimtype: 1-10V or push button		
	Cutout dimension (mm): 72		
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	- 1/2	☐
	Dimtype: 1-10V or DALI or push button		
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1/2(0) 1/2(0)	☐
	Dimtype: DALI		
	Cutout dimension (mm): 72		
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	1(1) 1(1/2)	☐
	Dimtype: 1-10V or DALI or push button		
	Cutout dimension (mm): 84		
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1/2(0) 0	☐
	Dimtype: 1-10V or push button		
	Cutout dimension (mm): 55		

MINIGRID IN TRIMLESS 2 HP 92720

100050 9210 W-B

	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	1/2(0) 0	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	1 1/2->1	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	1/2 1/2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1/2 1/2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1/2 1/2	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	1/2->1(1) 1/2->1(1/2)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	1/2 1/2	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	0 1/2	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	1/2 0	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	1/2	☐

DELTALIGHT

MINIGRID IN TRIMLESS 2 HP 92720

100050 9210 W-B



21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5

Dimtype: DALI

Cutout dimension (mm): 30

1/2 ☐

Mounting kits




202 71 95 02 HP MINIGRID IN 2 MOUNTING KIT HP

Cutout dimension (mm): 130 x 233

☐

Light altering devices



201 05 01 B HONEYCOMB 72 B

☐



201 05 04 SOFTENING LENS 72

☐

Notes: