
DELTALIGHT




BOXY 2 L 92733 DIM8

REFERENCE 10727 9228 W-W

AVAILABLE IN
ALU GRIS-GRIS ALU 10727 9228 A-A
NOIR-NOIR 10727 9228 B-B
NOIR-FLEMISH BRONZE 10727 9228 B-FBR
NOIR-FLEMISH GOLD 10727 9228 B-FG
BLANC-BLANC 10727 9228 W-W





View on website

General info	
LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non réglable
INFORMATION	2 x REFLECTOR FL-33° INCL.DIMMABLE POWER SUPPLY 350mA-DC >> B-MMAT only interior use - other colours also exterior use

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	fin de phase
ENERGY CLASS	D
CERTIFICATION	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
RVALUES	Rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1506lm // 11,6W // 129lm/W
LED TECHNICS (LUMINAIRE)	1201lm // 13,3W // 90lm/W

Accessories

BOXY HONEYCOMB
BOXY SOFTENING LENS
BOXY GLASS SBL

For detailed installation instructions, please consult the manual : **10727_XXXX_HAND.pdf**


DELTALIGHT

BOXY 2 L 92733 DIM8

10727 9228 W-W

FINISH YOUR SPECIFICATION

Equipements de contrôle divers




300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 40


☐

modifier les dispositifs de lumière




251 70 03 01 B BOXY HONEYCOMB B ☐

251 70 03 01 W BOXY HONEYCOMB W ☐



251 70 03 04 B BOXY SOFTENING LENS B ☐

251 70 03 04 W BOXY SOFTENING LENS W ☐



251 70 03 05 B BOXY GLASS SBL B ☐

251 70 03 05 W BOXY GLASS SBL W ☐

Notes: