





D-LINER 19 SBL LOC2 620 940 RD

32043 9400 B

AVAILABLE IN
BLACK 32043 9400 B



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 390mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 0,5m + WIELAND PLUG GST08i2 male green

Electrical info

CLASS	III
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 15W / CRI>90 (R9: 59) / 4000K / 1550lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	1550lm // 15W // 123lm/W
LED TECHNICS (LUMINAIRE)	1162lm // 17,2W // 67lm/W

Requirements

LED POWER SUPPLY SET LOC PARALLEL

Options

CONNECTING CABLE LOC PARALLEL

For detailed installation instructions, please consult the manual : [32043_XXX0_HAND.pdf](#)

DELTALIGHT

D-LINER 19 SBL LOC2 620 940 RD

32043 9400 B

CEILING COMPATIBILITY

Ceiling Type

Mounting Kit



Acoustic climate-control ceiling Interlu WEC

FINISH YOUR SPECIFICATION


Emergency units

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5

Dimtype: DALI

1

Current supply



32010 1200 T CONNECTOR LOC PARALLEL



32010 1310 CONNECTING CABLE LOC PARALLEL 1m



32010 1320 CONNECTING CABLE LOC PARALLEL 2m



32010 1330 CONNECTING CABLE LOC PARALLEL 3m



32010 1340 CONNECTING CABLE LOC PARALLEL 4m

DELTALIGHT

D-LINER 19 SBL LOC2 620 940 RD

32043 9400 B



32010 1350 CONNECTING CABLE LOC PARALLEL 5m


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



32010 0095 LED POWER SUPPLY SET LOC PARALLEL 390mA / 35W DIM5

1


Dimtype: DALI



32010 0125 LED POWER SUPPLY SET LOC PARALLEL 780mA / 35W DIM5

2->2


Dimtype: DALI



32010 0155 LED POWER SUPPLY SET LOC PARALLEL 1170mA / 100W DIM5

3->3


Dimtype: DALI



32010 0425 LED POWER SUPPLY SET LOC PARALLEL 1560mA / 100W DIM5

4->4

Dimtype: DALI



32010 0445 LED POWER SUPPLY SET LOC PARALLEL 1950mA / 100W DIM5

5->5

Dimtype: DALI

Notes: