DELTALIGHT



SPY 66 93018 ADM DIM5

REFERENCE 24625 9315 FW

AVAILABLE IN
BLACK 24625 9315 B
FULL WHITE 24625 9315 FW
WHITE 24625 9315 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Mains voltage track Mains voltage track mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° 3F MULTI DIMMABLE POWER ADAPTER 700mA Optional REFLECTORS 30° & 45° available

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 25W / CRI>90 (R9: 52) / 3000K / 2811lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	2811lm // 25W // 112lm/W
LED TECHNICS (LUMINAIRE)	2007lm // 29W // 70lm/W

Requirements

SPY 66 TUBE
TRACK 3F DIM

Accessories

HONEYCOMB 57

For detailed installation instructions, please consult the manual : **24625_XXX5_HAND.pdf**

DELTALIGHT

SPY 66 93018 ADM DIM5

24625 9315 FW

FINISH YOUR SPECIFICATION

Light altering devices



24611 0150 B HONEYCOMB 57 SINGLE USE B ☐

Finish your product



24611 0100 B SPY 66 TUBE B ☐

24611 0100 FBR SPY 66 TUBE FBR ☐

24611 0100 FG SPY 66 TUBE FG ☐

24611 0100 GC SPY 66 TUBE GC ☐

24611 0100 W SPY 66 TUBE W ☐

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18° ☐



24611 0230 SPY 66 REFLECTOR 30° ☐



24611 0240 SPY 66 REFLECTOR 45° ☐

DELTALIGHT

SPY 66 93018 ADM DIM5

24625 9315 FW

COMPATIBLE TRACKS

TRACK 3F DIM H			Available Colours
200 14 410 TRACK 3F DIM H 1m	1000 m	1.6 kg	
200 14 420 TRACK 3F DIM H 2m	2000 m	3.2 kg	
200 14 430 TRACK 3F DIM H 3m	3000 m	4.8 kg	

TRACK 3F DIM IN			Available Colours
200 13 410 TRACK 3F DIM IN 1m	1000 m	1.2 kg	
200 13 420 TRACK 3F DIM IN 2m	2000 m	2.4 kg	
200 13 430 TRACK 3F DIM IN 3m	3000 m	3.5 kg	

TRACK 3F DIM ON			Available Colours
200 12 410 TRACK 3F DIM ON 1m	1000 m	1.1 kg	
200 12 420 TRACK 3F DIM ON 2m	2000 m	2.1 kg	
200 12 430 TRACK 3F DIM ON 3m	3000 m	3.1 kg	

Notes: