DELTALIGHT

OML50 - PRISMATIC LENS D HO CORNER R420 90° 930 DIM5

REFERENCE 31653 9305 B

AVAILABLE IN
BLACK 31653 9305 B

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	10
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 15,5W / CRI>90 (R9: 50) / 3000K / 2380lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	2380lm // 15,5W // 153lm/W

Options

WIRELESS CONTROL DIM5

Notes:

Delta Light NV may revise the information and technical data at any time without notice. Version: 08/10/2026