SUPERLOOP-XY180 MDL

Used with the Superloop Deltalight custom engineered 48V low voltage track. XY180 is a 3-piece lighting collection designed by OMA. The collection was inspired by a fascination with point, line and surface; key architectural elements. The ceiling lights are meant for individual and shared workspaces, but can also beapplied to domestic and public interior spaces.

Specification	
Installation Method:	4" junction box
Adjustability:	Adjustable 0-180° / 360°
Rating:	IP20

Performance	
CRI:	90
*Standard Power:	10W

Delivered Lumens	3000K
Superloop-XY180 MDL:	874lm

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: XY1T-SP30A-B-SLP-MDL

Luminaire	Shape	Power*		CCT	Finish	Application[1]
OXY XY180	**1T** Single LED Tube (530mm / 20⅞")	**SP** Standard Power	–	**30** 3000K	**B** Black	**SLP-MDL** Superloop MDL

1 For use on Superloop MDL; 48V power supplied with Superloop MDL.

Related Products

Superloop-Fix MDL, Superloop-Spy MDL, Superloop-Vizir/Hedra MDL, XY180, Punk C (pendant), Orbit Punk (wall)

Finish Options

SUPERLOOP-XY180 MDL



BLACK
(shown on Superloop MDL)

Photometric Data

SUPERLOOP-XY180 MDL



Installation Options

Delta Light's Superloop suspended track system utilizes 48V power supplies. With several power options available, the below details maximum luminaire modules per power supply by type.

Maximum Capacity per Remote Power Supply	Power Box L	Power Box H	Remote Power Supply
*Superloop-XY180 MDL: 8	5	8	8

FOR SYSTEM HARDWARE, REFER TO THE FOLLOWING:
Superloop MDL (suspended rings, rectangles, & squares)

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.