



SUPERLOOP HC 350 SBL 930

20552 9300 FG



AVAILABLE IN

NOIR 20552 9300 B

FLEMISH BRONZE 20552 9300 FBR

FLEMISH GOLD 20552 9300 FG

BLANC 20552 9300 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	11.3
ADJUSTABILITY	non réglable
INFORMATION	INCL.PC SBL 4 SEGMENTS EXCL.LED POWER SUPPLY 24-DC INCL.8 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.4 x CABLE 2 x 0.75mm ²

Electrical info

ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED FLEX FP 40,5W / CRI>90 / 3000K / 4900,5lm)
LED TECHNICS (LIGHT SOURCE)	19602 lm // 162 W // 121 lm/W
LED TECHNICS (LUMINAIRE)	8821lm // 186,3W // 47lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90


CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [20552_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

le cable d'alimentation

	<u>203 99 55 ANO</u> CABLE BASE R ANO	☐
	<u>203 99 55 B</u> CABLE BASE R B	☐
	<u>203 99 55 W</u> CABLE BASE R W	☐
	<u>203 99 56 ANO</u> CABLE BASE S ANO	☐
	<u>203 99 56 B</u> CABLE BASE S B	☐
	<u>203 99 56 W</u> CABLE BASE S W	☐


les alimentations led

of Fixtures



web2print_power_supply_info_box

Min current | Max current




300 89 24 60

LED POWER SUPPLY 24V-DC / 60W

1/4 ☐

Dimtype: non dimmable

Cutout dimension (mm): 55




300 89 24 61

LED POWER SUPPLY 24V-DC / 60W DIN

1/4 ☐

Dimtype: non dimmable



300 89 24 80 ED1

LED POWER SUPPLY 24V-DC / 80W DIM1

1/4 ☐











Dimtype: 1 à 10 V

Cutout dimension (mm): 75

DELTALIGHT

SUPERLOOP HC 350 SBL 930







20552 9300 FG

	<u>300 89 24 150</u>	LED POWER SUPPLY 24V-DC / 150W	2/4	☐
	Dimtype: non dimmable			
	Cutout dimension (mm): 75			
	<u>300 89 24 480</u>	LED POWER SUPPLY 24V-DC / 480W DIN	2	☐
	Dimtype: non dimmable			
	<u>300 90 003 ED1</u>	24V-DC / 4A DIM1 UNIT	1/3	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 30			
	<u>300 90 003 ED5</u>	24V-DC / 4A DIM5 UNIT	1/3	☐
	Dimtype: DALI			
	Cutout dimension (mm): 30			
	<u>300 90 010</u>	24V-DC / 2 x 4A WIRELESS DIM UNIT	2/3	☐
	Dimtype: WDL = dimmable sans fil			
	<u>21012 0101</u>	LED POWER SUPPLY 24V-DC / 60W IP67 DIM1	1/4	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 65			
	<u>21012 0111</u>	LED POWER SUPPLY 24V-DC / 90W IP67 DIM1	1/4	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 75			
	<u>21012 0121</u>	LED POWER SUPPLY 24V-DC / 120W IP67 DIM1	2/4	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 75			
	<u>21012 0135</u>	LED POWER SUPPLY 24V-DC / 60W IP67 DIM5	1/4	☐
	Dimtype: DALI			
	Cutout dimension (mm): 65			
	<u>21012 0145</u>	LED POWER SUPPLY 24V-DC / 90W IP67 DIM5	1/4	☐
	Dimtype: DALI			
	Cutout dimension (mm): 75			


DELTA LIGHT


SUPERLOOP HC 350 SBL 930

20552 9300 FG

	21012 0155 LED POWER SUPPLY 24V-DC / 120W IP67 DIM5 Dimtype: DALI Cutout dimension (mm): 75	2/4 ☐
	21012 0171 LED POWER SUPPLY 24V-DC / 60W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 61	1/4 ☐
	21012 0181 LED POWER SUPPLY 24V-DC / 90W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 70	1/4 ☐
	21012 0191 LED POWER SUPPLY 24V-DC / 120W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 70	2/4 ☐
	21012 0205 LED POWER SUPPLY 24V-DC / 60W DIM5 Dimtype: DALI Cutout dimension (mm): 61	1/4 ☐
	21012 0225 LED POWER SUPPLY 24V-DC / 100W DIM5 Dimtype: DALI Cutout dimension (mm): 70	1/4 ☐

Equipements de contrôle divers	# of Fixtures
 web2print_power_supply_info_box	Min current Max current






	300 90 24 ED2 LED DIMMODULE 24V / 3CH / 6A DIM2 Dimtype: DALI ou bouton poussoir	2/4 ☐
--	---	------------------------------

les sets pour recouvrement plafond		
	<u>204 00 62 ANO</u> COVERSET R 62 ANO	☐

DELTA LIGHT

SUPERLOOP HC 350 SBL 930

20552 9300 FG

	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐

DELTALIGHT

SUPERLOOP HC 350 SBL 930

20552 9300 FG


204 90 90 B COVERSET S 90 B

☐

204 90 90 W COVERSET S 90 W

☐


les accessoires de suspension



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0340 B SUSPENSION ST B


☐

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

☐


les accessoires pour connexions électriques



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: