
DELTALIGHT




SUPERLOOP HC 350 SBL 930

REFERENCE 20552 9300 FG

AVAILABLE IN
SCHWARZ 20552 9300 B
FLEMISH BRONZE 20552 9300 FBR
FLEMISH GOLD 20552 9300 FG
WEISS 20552 9300 W





View on website

General info	
LOCATION	innenbereich
INSTALLATION	Decke Pendel
INGRESS PROTECTION	IP20
WEIGHT (KG)	11.3
ADJUSTABILITY	nicht verstellbar
INFORMATION	INCL.PC SBL 4 SEGMENTS EXCL.LED POWER SUPPLY 24-DC INCL.8 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.4 x CABLE 2 x 0.75mm²

Electrical info	
ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	Abhängig von der Art der externen Stromversorgung
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED FLEX FP 40,5W / CRI>90 / 3000K / 4900,5lm)
LED TECHNICS (LIGHT SOURCE)	19602 lm // 162 W // 121 lm/W
LED TECHNICS (LUMINAIRE)	8821lm // 186,3W // 47lm/W

Requirements

LED POWER SUPPLY 24V-DC

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : **20552_XXX0_HAND.pdf**


DELTALIGHT

SUPERLOOP HC 350 SBL 930

20552 9300 FG

FINISH YOUR SPECIFICATION


Stromversorgung



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐



203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐


203 99 56 W CABLE BASE S W ☐

LED Betriebsgeräte

# of Fixtures

Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 24 60 LED POWER SUPPLY 24V-DC / 60W 1/4 ☐


Dimtype: nicht dimmbar

Cutout dimension (mm): 55



300 89 24 61 LED POWER SUPPLY 24V-DC / 60W DIN 1/4 ☐

Dimtype: nicht dimmbar




300 89 24 80 ED1 LED POWER SUPPLY 24V-DC / 80W DIM1 1/4 ☐

Dimtype: 1-10V

Cutout dimension (mm): 75

SUPERLOOP HC 350 SBL 930


20552 9300 FG



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W 2/4


Dimtype: nicht dimmbar

Cutout dimension (mm): 75



300 89 24 480 LED POWER SUPPLY 24V-DC / 480W DIN 2


Dimtype: nicht dimmbar



300 90 003 ED1 24V-DC / 4A DIM1 UNIT 1/3

Dimtype: 1-10V


Cutout dimension (mm): 30



300 90 003 ED5 24V-DC / 4A DIM5 UNIT 1/3


Dimtype: DALI

Cutout dimension (mm): 30



300 90 010 24V-DC / 2 x 4A WIRELESS DIM UNIT 2/3


Dimtype: WDL = Drahtlos dimmbar



21012 0101 LED POWER SUPPLY 24V-DC / 60W IP67 DIM1 1/4

Dimtype: 1-10V


Cutout dimension (mm): 65



21012 0111 LED POWER SUPPLY 24V-DC / 90W IP67 DIM1 1/4

Dimtype: 1-10V


Cutout dimension (mm): 75



21012 0121 LED POWER SUPPLY 24V-DC / 120W IP67 DIM1 2/4

Dimtype: 1-10V


Cutout dimension (mm): 75



21012 0135 LED POWER SUPPLY 24V-DC / 60W IP67 DIM5 1/4

Dimtype: DALI

Cutout dimension (mm): 65



21012 0145 LED POWER SUPPLY 24V-DC / 90W IP67 DIM5 1/4


Dimtype: DALI

Cutout dimension (mm): 75

DELTALIGHT

SUPERLOOP HC 350 SBL 930


20552 9300 FG



21012 0155 LED POWER SUPPLY 24V-DC / 120W IP67 DIM5 2/4

Dimtype: DALI


Cutout dimension (mm): 75



21012 0171 LED POWER SUPPLY 24V-DC / 60W DIM1 1/4

Dimtype: 1-10V


Cutout dimension (mm): 61



21012 0181 LED POWER SUPPLY 24V-DC / 90W DIM1 1/4

Dimtype: 1-10V


Cutout dimension (mm): 70



21012 0191 LED POWER SUPPLY 24V-DC / 120W DIM1 2/4

Dimtype: 1-10V


Cutout dimension (mm): 70



21012 0205 LED POWER SUPPLY 24V-DC / 60W DIM5 1/4

Dimtype: DALI

Cutout dimension (mm): 61



21012 0225 LED POWER SUPPLY 24V-DC / 100W DIM5 1/4

Dimtype: DALI


Cutout dimension (mm): 70

Sonstige Steuergeräte

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.








300 90 24 ED2 LED DIMMODULE 24V / 3CH / 6A DIM2 2/4

Dimtype: DALI / Taster

SUPERLOOP HC 350 SBL 930


20552 9300 FG

Coverset



	**204 00 62 ANO**	COVERSET R 62 ANO
	204 00 62 B	COVERSET R 62 B
	204 00 62 W	COVERSET R 62 W
	**204 00 90 ANO**	COVERSET R 90 ANO
	204 00 90 B	COVERSET R 90 B
	204 00 90 W	COVERSET R 90 W
	**204 00 100 ANO**	COVERSET R 100 ANO
	204 00 100 B	COVERSET R 100 B
	204 00 100 W	COVERSET R 100 W
	**204 62 62 ANO**	COVERSET S 62 ANO
	204 62 62 B	COVERSET S 62 B
	204 62 62 W	COVERSET S 62 W
	**204 80 80 ANO**	COVERSET S 80 ANO
	204 80 80 B	COVERSET S 80 B

SUPERLOOP HC 350 SBL 930



20552 9300 FG

	204 80 80 W COVERSET S 80 W	☐
	**204 90 90 ANO** COVERSET S 90 ANO	☐
	204 90 90 B COVERSET S 90 B	☐
	204 90 90 W COVERSET S 90 W	☐

Aufhängung Zubehör

	**328 10 01** SUSPENSION TRIMLESS O.F.A. **Cutout dimension (mm): 62 (CONCRETE: 102)**	☐
	**15225 0340 B** SUSPENSION ST B **Cutout dimension (mm): 27**	☐
	15225 0340 W SUSPENSION ST W	☐

elektrische Anschlussteile

	**328 10 03** CONNECTION TRIMLESS O.F.A. **Cutout dimension (mm): 62 (CONCRETE: 102)**	☐
	**15225 0360 B** CONNECTION ST B **Cutout dimension (mm): 43**	☐
	15225 0360 W CONNECTION ST W	☐

DELTALIGHT

SUPERLOOP HC 350 SBL 930

20552 9300 FG

Notes: