
DELTALIGHT



SPM52 - PROFILE 3m

REFERENZEN 420 52 30 00 B

ERHÄLTLICH IN
SCHWARZ 420 52 30 00 B



Auf der Website anzeigen


Allgemeine Information	
ANWENDUNGSBEREICH	innenbereich
INSTALLATION	Decke Einbau,Wand Einbau
FORM / GRÖSSE DES AUSSCHNITTS (MM)	rechteck - 121 x (L + 5)
EINBAUTIEFE (MM)	150
DICKE DER BEFESTIGUNGSFLÄCHE (MM)	max.12
GEWICHT (KG)	11.4
INFORMATION	L : 3m 2 x 48V conductors 2 DIM CONDUCTORS (For individual DALI dimming)

Elektrische Informationen	
KLASSE	III

Detaillierte Installationsanweisungen finden Sie in der Montageanleitung : **420_52_30_00_HAND.pdf**


KOMPATIBLE TEILE

Befestigungskomponenten



420 52 98 01 SPM52 - SUSPENSION BRACKET


Eckverbinder




420 06 01 SPM - CORNER 180°

SPM52 - PROFILE 3m

420 52 30 00 B




420 52 06 06 SPM52 - CORNER SET 90°




420 52 06 17 SPM52 - CORNER SET V90°

Endkappen




420 52 03 01 SPM52 - END CAP SET


LED Betriebsgeräte




300 89 48 90 LED POWER SUPPLY 48V-DC / 90W




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN




300 89 48 150 LED POWER SUPPLY 48V-DC / 150W



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN



21012 0230 LED POWER SUPPLY 48V-DC / 100W




21012 0240 LED POWER SUPPLY 48V-DC / 200W


SPM52 - PROFILE 3m

420 52 30 00 B


Profile



420 52 10 00 SPM52 - PROFILE 1m




420 52 20 00 SPM52 - PROFILE 2m




420 52 30 00 SPM52 - PROFILE 3m

SMART 48




300 90 011 SMART 48 MODULATOR DIM9




300 90 012 SMART 48 MODULATOR WD


Spezielle Komponenten




200 12 01 TRACK 3F DIM CUTTING TOOL



21032 0040 M - WIRELESS PRESENCE AND DAYLIGHT SENSOR



21032 0185 M - DALI PRESENCE AND DAYLIGHT SENSOR (BROADCAST)




21032 0190 M - WIRELESS SENSOR HUB


SPM52 - PROFILE 3m

420 52 30 00 B


Stromversorgung




420 99 01 SPM - CONNECTOR 48V - 180°



420 99 02 SPM - CONNECTOR 48V - 0-180°




420 99 03 SPM - SUPPLY 48V




21032 0030 SMART 48 MODULATOR PLUG-IN WD

KOMPATIBLE LEUCHTEN

DUMMY




421 158 811 92 MDL M52 - SPY FOCUS 927 MDL




421 158 811 93 MDL M52 - SPY FOCUS 930 MDL

SPLITLINE M/SHIFTLINE M - CUPPA



28814 9035 M - CUPPA C SOFT 93040 DIM5


SPLITLINE M/SHIFTLINE M - GIBBO



421 622 811 920 MDL M - GIBBO 927 MDL


SPM52 - PROFILE 3m

420 52 30 00 B




421 622 811 930 MDL M - GIBBO 930 MDL

SPLITLINE M/SHIFTLINE M - HEDRA 39 C




22539 9235 M - HEDRA 39 C 92745 DIM5




22539 9335 M - HEDRA 39 C 93045 DIM5

SPLITLINE M/SHIFTLINE M - MICROSPY 39 C




421 612 811 921 MDL M - MICROSPY 39 C 92745 MDL




421 612 811 931 MDL M - MICROSPY 39 C 93045 MDL

SPLITLINE M52 - 2 LED




421 248 2822 MDL M52 - 2 LED OK 82720 MDL




421 248 2832 MDL M52 - 2 LED OK 83020 MDL

SPLITLINE M52 - LED



421 228 811 922 D MDL M52 - 1 LED D 92733 MDL




421 228 811 932 D MDL M52 - 1 LED D 93033 MDL


SPM52 - PROFILE 3m

420 52 30 00 B

SPLITLINE M52 - MIDISPY




421 138 272 822 MDL M52 - MIDISPY 82720 MDL




421 138 272 832 MDL M52 - MIDISPY 83020 MDL


SPLITLINE M52 - SPY




421 148 811 921 MDL M52 - SPY 92718 MDL



421 148 811 922 MDL M52 - SPY 92733 MDL




421 148 811 931 MDL M52 - SPY 93018 MDL




421 148 811 932 MDL M52 - SPY 93033 MDL

SPLITLINE M52 - SPY 39




24454 9025 M52 - SPY 391 SOFT 93020 DIM5



24454 9035 M52 - SPY 391 SOFT 93040 DIM5


SPLITLINE M52 - SPY 39 L



24456 9025 M52 - SPY 391 L SOFT 93020 DIM5


SPM52 - PROFILE 3m

420 52 30 00 B




24456 9035 M52 - SPY 391 L SOFT 93040 DIM5


SPLITLINE M52 - SPY 52



24452 9025 M52 - SPY 52 SOFT 93020 DIM5




24452 9035 M52 - SPY 52 SOFT 93045 DIM5




24452 9045 M52 - SPY 52 SOFT 93030 DIM5


SPLITLINE M52 - SPY 66



24446 9015 M52 - SPY 66 TW 96518 DIM5




24446 9025 M52 - SPY 66 TW 96530 DIM5




24446 9035 M52 - SPY 66 TW 96545 DIM5

SPLITLINE M52 - SPY FOCUS



24429 9205 M52 - SPY FOCUS LP 927 DIM5




24429 9305 M52 - SPY FOCUS LP 930 DIM5

SPM52 - PROFILE 3m


420 52 30 00 B

SPLITLINE M52 profile




420 52 20 00 SPM52 - PROFILE 2m


SPY II 39 M CABLE




12306622MD00-90D2M4 SPY II 39 M CABLE SOFT CRI90 3000-1800K 26° MDL



12306622MD00-90D2S7 SPY II 39 M CABLE SOFT CRI90 3000-1800K 19° MDL




12306622MD00-90D2V1 SPY II 39 M CABLE SOFT CRI90 3000-1800K 55° MDL




12306622MD00-90D2W1 SPY II 39 M CABLE SOFT CRI90 3000-1800K 35° MDL


SPY II 39 M52




123061230500-90T1M4 SPY II 39 M52 TW CRI90 1800-4000K 26° DALI DIM



123061230500-90T1S7 SPY II 39 M52 TW CRI90 1800-4000K 19° DALI DIM



123061230500-90T1V1 SPY II 39 M52 TW CRI90 1800-4000K 55° DALI DIM




123061230500-90T1W1 SPY II 39 M52 TW CRI90 1800-4000K 35° DALI DIM


SPM52 - PROFILE 3m

420 52 30 00 B


SPY II 39 M52 FOCUS




12306231MD00-9027AB SPY II 39 M52 FOCUS CRI90 2700K MDL




12306231MD00-9030AB SPY II 39 M52 FOCUS CRI90 3000K MDL




12306231MD00-9035AB SPY II 39 M52 FOCUS CRI90 3500K MDL




12306231MD00-9040AB SPY II 39 M52 FOCUS CRI90 4000K MDL




12306231MD00-9727AB SPY II 39 M52 FOCUS CRI97 2700K MDL



12306231MD00-9730AB SPY II 39 M52 FOCUS CRI97 3000K MDL




12306231MD00-9735AB SPY II 39 M52 FOCUS CRI97 3500K MDL



12306231MD00-9740AB SPY II 39 M52 FOCUS CRI97 4000K MDL


SPY II 39 M52 FRAMER




12306341MD00-902700 SPY II 39 M52 FRAMER CRI90 2700K MDL

SPM52 - PROFILE 3m


420 52 30 00 B




12306341MD00-903000 SPY II 39 M52 FRAMER CRI90 3000K MDL




12306341MD00-903500 SPY II 39 M52 FRAMER CRI90 3500K MDL




12306341MD00-904000 SPY II 39 M52 FRAMER CRI90 4000K MDL




12306341MD00-972700 SPY II 39 M52 FRAMER CRI97 2700K MDL



12306341MD00-973000 SPY II 39 M52 FRAMER CRI97 3000K MDL




12306341MD00-973500 SPY II 39 M52 FRAMER CRI97 3500K MDL



12306341MD00-974000 SPY II 39 M52 FRAMER CRI97 4000K MDL

SPY II 39 M52 WALLWASH



12306452MD00-90D200 SPY II 39 M52 WALLWASH SOFT CRI90 3000K-1800K MDL

Notes: