


27328 9205 GC

Technical drawing of a mechanical part, likely a bracket or support. The drawing shows a side view of a component with a cylindrical feature. Dimensions are indicated: 160 (total length), 7 (thickness), 20 (width of a step), 11 (height of a base), 92 (length of the cylindrical part), and Ø39 (diameter of the cylindrical part). A circular feature is shown with a centerline and a dimension of 0.85° ± 5°.



[View on website](#)



LED POWER SUPPLY 48V-DC

Delta Light NV may revise the information and technical data at any time without notice. Version: 29/04/2026



SPL14 - SPY 39 FOCUS 927 DIM5

27328 9205 GC

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	10	
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	24	
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	10	
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	20	

COMPATIBLE COMPOSABLES

SPLITLINE 14 profile	Available Colours
 27300 0020 SPL14 - PROFILE 2m	
 27300 0030 SPL14 - PROFILE 3m	

Notes:

DELTALIGHT

SPL14 - SPY 39 FOCUS 927 DIM5

27328 9205 GC