
DELTALIGHT




KIX II 927

REFERENCE 13533 9200 A

AVAILABLE IN
ALU GREY 13533 9200 A
ANTHRACITE 13533 9200 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1.1
ADJUSTABILITY	0° to 90° swiveling
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	120°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	576lm // 6,7W // 86lm/W

Accessories

KAP KIX
HONEYCOMB KIX

For detailed installation instructions, please consult the manual : **13533_XXX0_HAND.pdf**


DELTALIGHT

KIX II 927


13533 9200 A

FINISH YOUR SPECIFICATION

Light altering devices



232 10 00 N KAP KIX N ☐



232 10 03 N HONEYCOMB KIX N ☐

Notes: