





FRAX MB POLE 93026
HONEYCOMB

26021 9320 N

AVAILABLE IN
ANTHRACITE 26021 9320 N



 [View on website](#)



General info

LOCATION	outdoor
INSTALLATION	Pole Pole top
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.3
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	9 x LENS SP-14° INCLLED POWER SUPPLY 900mA-DC INCL.BEAM LENS 26° INCL.HONEYCOMB INCL.1 x CABLE H05 RN-F 3 x 1mm² 6m

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 23,4W / CRI>90 (R9: 64) / 3000K / 2654lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	26°
LED TECHNICS (LIGHT SOURCE)	2654lm // 23,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	1486lm // 26,9W // 55lm/W

Requirements

FRAX BRACKET

Options

FRAX ANTI VANDAL SCREWS


Accessories

FRAX M KAP

For detailed installation instructions, please consult the manual : [26021_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Light altering devices




26070 0020 N FRAX M KAP N

☐


Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐

26071 0050 N FRAX POLE 60 BRACKET N

☐

26071 0060 N FRAX POLE 80 BRACKET N

☐

Notes: