





SUPERLOOP HC SBL OVAL M 930

REFERENCE 20571 9300 W

AVAILABLE IN
BLACK 20571 9300 B
FLEMISH BRONZE 20571 9300 FBR
FLEMISH GOLD 20571 9300 FG
WHITE 20571 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 900-1200mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 36,3-49,5W / CRI>90 (R9: 59) / 3000K / 5217-6845lm
SDCM	SDCM3
LM80	L70 > 20000
LED TECHNICS (LIGHT SOURCE)	6845lm // 49,5W // 138lm/W
LED TECHNICS (LUMINAIRE)	4113lm // 56,9W // 72lm/W

Requirements

LED POWER SUPPLY 900 / 1200mA-DC DIM
 SUPERLOOP POWERBOX H 900mA
 SUPERLOOP POWERBOX H 1200mA

Options

CABLE BASE R / S
 COVERSET R 62-90-100 / S 62-80-90
 CONNECTION ST / CONNECTION TRIMLESS
 SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [20571_XXX0_HAND.pdf](#)


DELTA LIGHT

SUPERLOOP HC SBL OVAL M 930

20571 9300 W

FINISH YOUR SPECIFICATION

Current supply



	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Power box

of Fixtures

Min current | Max current


 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

	321 55 312 ED1 B SUPERLOOP POWERBOX H8 1200mA DIM1 B	1	☐
	321 55 312 ED1 W SUPERLOOP POWERBOX H8 1200mA DIM1 W	1	☐
	20548 0015 B SUPERLOOP POWERBOX H9 900mA DIM5 B	1	☐
	20548 0015 W SUPERLOOP POWERBOX H9 900mA DIM5 W	1	☐

DELTALIGHT

SUPERLOOP HC SBL OVAL M 930

20571 9300 W



	20548 0025 B SUPERLOOP POWERBOX H9 1200mA DIM5 B	1	☐
	20548 0025 W SUPERLOOP POWERBOX H9 1200mA DIM5 W	1	☐

LED power supplies



of Fixtures

Min current | Max current

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

	300 90 129 LED POWER SUPPLY 900mA-DC / 60W DIM5	1	☐
	300 90 130 LED POWER SUPPLY 1200mA-DC / 60W DIM5	1	☐
	300 90 132 LED POWER SUPPLY 1200mA-DC / 70W DIM1	1	☐





Coversets

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐
	204 00 90 ANO COVERSET R 90 ANO	☐

DELTALIGHT

SUPERLOOP HC SBL OVAL M 930

20571 9300 W



	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTALIGHT


SUPERLOOP HC SBL OVAL M 930

20571 9300 W

Suspension parts

	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0340 B SUSPENSION ST B	☐
Cutout dimension (mm): 27		
	15225 0340 W SUSPENSION ST W	☐

Electric connection parts

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0360 B CONNECTION ST B	☐
Cutout dimension (mm): 43		
	15225 0360 W CONNECTION ST W	☐

Notes: