



ENTERO RD-L TW 96545



28420 9030 GC

AVAILABLE IN

BLACK 28420 9030 B

FULL WHITE 28420 9030 FW

GOLD COLOURED 28420 9030 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 112
RECESSED DEPTH (MM)	160
THICKNESS OF MOUNTING SURFACE (MM)	max.16
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.67
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 18° & 30° available

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 2700K-6500K / 2054lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2054lm // 17,8W // 116lm/W
LED TECHNICS (LUMINAIRE)	1617lm // 20,5W // 79lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW

Options

ENTERO RD-L MOUNTING SET S2

Accessories

ENTERO L HONEYCOMB
ENTERO L LINEAR SPREAD LENS
ENTERO L SPREAD LENS
ENTERO L SOFTENING LENS
ENTERO L GLASS SBL


For detailed installation instructions, please consult the manual : [28420_XXX0_HAND.pdf](#)





CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	 28500 0210 - ENTERO RD-L MOUNTING SET S2 Required
 Concrete + plaster	 28500 0210 - ENTERO RD-L MOUNTING SET S2 Required
 Lintel + plaster	 28500 0210 - ENTERO RD-L MOUNTING SET S2 Required
 Hollow-core slab	 28500 0210 - ENTERO RD-L MOUNTING SET S2 Required
 Hollow-core slab + plaster	 28500 0210 - ENTERO RD-L MOUNTING SET S2 Required
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

LED power supplies	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current

 21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5	1 ☐
Dimtype: DALI	
Cutout dimension (mm): 85	


 28500 0130 ENTERO L LINEAR SPREAD LENS	☐
 28500 0140 ENTERO L SPREAD LENS	☐
 28500 0150 ENTERO L SOFTENING LENS	☐
 28500 0160 ENTERO L GLASS SBL	☐
 28500 0170 B ENTERO L HONEYCOMB SINGLE USE B	☐
 28500 0180 B ENTERO L HONEYCOMB DOUBLE USE B	☐

DELTALIGHT

ENTERO RD-L TW 96545

28420 9030 GC

Mounting set S2



28500 0210 ENTERO RD-L MOUNTING SET S2



Notes: