



ENTERO SQ-M TRIMLESS IP TW 94030



28573 9020 B

AVAILABLE IN

BLACK 28573 9020 B

FULL WHITE 28573 9020 FW

GOLD COLOURED 28573 9020 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - Ø KIT
RECESSED DEPTH (MM)	150
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.405
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	979lm // 9W // 109lm/W
LED TECHNICS (LUMINAIRE)	638lm // 10,4W // 62lm/W

Requirements

MOUNTING KIT ENTERO SQUARE M

LED POWER SUPPLY 500mA-DC TW (Remote)

For detailed installation instructions, please consult the manual : [28573_XXX0_HAND.pdf](#)

ENTERO SQ-M TRIMLESS IP TW 94030


28573 9020 B


CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Plasterboard	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Stucanet	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Wood	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Concrete + plaster	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Lintel + plaster	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Hollow-core slab + plaster	 28400 0050 - MOUNTING KIT ENTERO SQ-M Required
 Stretched ceiling	 28400 0110 - MOUNTING KIT ENTERO SQ-M CSC Required
	 28400 0170 - MOUNTING KIT ENTERO SQ-M WSC Required

FINISH YOUR SPECIFICATION

LED power supplies	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the 'I' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current

	21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5	2
	Dimtype: DALI	
	Cutout dimension (mm): 85	


Mounting kits		
	28400 0050 MOUNTING KIT ENTERO SQ-M	
Cutout dimension (mm): 122 x 122		

DELTALIGHT

ENTERO SQ-M TRIMLESS IP TW 94030

28573 9020 B

Mounting kits stretched ceiling



28400 0110 MOUNTING KIT ENTERO SQ-M CSC



28400 0170 MOUNTING KIT ENTERO SQ-M WSC



Notes: