
DELTALIGHT




INFORM 40 SQ 160 DOWN 94063 DIM5

REFERENCE 30711 9435 W-B

AVAILABLE IN
BLACK-BLACK 30711 9435 B-B
WHITE-BLACK 30711 9435 W-B





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT6) Power selection to be set on driver EXCL.CABLE SUSPENSION

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	HO: LED cluster 27W / CRI>90 (R9: 50) / 4000K / 3987lm Or LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	HO: 3987lm // 27W // 148lm/W Or 2643lm // 16,3W // 162lm/W
LED TECHNICS (LUMINAIRE)	HO: 2759lm // 31W // 89lm/W Or 1829lm // 19W // 98lm/W

Options

INF40 SQ 160/180 - SUSPENSION SET
CABLE BASE R / S

DELTALIGHT


INFORM 40 SQ 160 DOWN 94063 DIM5

30711 9435 W-B

For detailed installation instructions, please consult the manual : **30711_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION


Current supply



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W




203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B


203 99 56 W CABLE BASE S W

Fixation components



30710 0010 B INF40 SQ 160/180 - SUSPENSION SET 1,6m B

30710 0010 W INF40 SQ 160/180 - SUSPENSION SET 1,6m W



30710 0030 B INF40 SQ 160/180 - SUSPENSION SET 3,0m B

30710 0030 W INF40 SQ 160/180 - SUSPENSION SET 3,0m W

DELTALIGHT

INFORM 40 SQ 160 DOWN 94063 DIM5

30711 9435 W-B

Notes: