


27328 9305 B

Technical drawing of a mechanical part, likely a bracket or support. The drawing shows a side view of a component with a cylindrical feature. Dimensions are indicated: 160 (total length), 7 (thickness), 20 (width of a step), 11 (height of a base), 92 (length of the cylindrical part), and Ø39 (diameter of the cylindrical part). A circular feature is shown with a dimension of 0.85° ± 5°.





LED POWER SUPPLY 48V-DC

Delta Light NV may revise the information and technical data at any time without notice. Version: 29/04/2026



SPL14 - SPY 39 FOCUS 930 DIM5

27328 9305 B

TERMINEZ VOTRE SPÉCIFICATION

les alimentations led		# de luminaires
 # de luminaires indique combien d'appareils peuvent être raccordés (min -> max) à l'alimentation. Les valeurs avant et après le ' ' correspondent respectivement au courant de pilotage minimal et maximal. Les valeurs entre parenthèses s'appliquent au 110V.		Courant min. Courant max.
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	Type de gradation: non dimmable	10
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	Type de gradation: non dimmable	24
 21012 0230 LED POWER SUPPLY 48V-DC / 100W	Type de gradation: non dimmable Dimension de découpe (mm): 40	10
 21012 0240 LED POWER SUPPLY 48V-DC / 200W	Type de gradation: non dimmable Dimension de découpe (mm): 40	20

COMPOSABLES COMPATIBLES

SPLITLINE 14 profile	Couleurs disponibles
 27300 0020 SPL14 - PROFILE 2m	
 27300 0030 SPL14 - PROFILE 3m	

Notes:

DELTALIGHT

SPL14 - SPY 39 FOCUS 930 DIM5

27328 9305 B