


27328 9305 B

Technical drawing of a mechanical part, likely a bracket or support. The drawing shows a cylindrical component with a diameter of $\varnothing 39$ and a length of 92. A bracket is attached to the side, with a width of 160 and a height of 7. A curved arrow indicates a rotation of 0.85° to 35° .



Bekijk op website

LED POWER SUPPLY 48V-DC

Delta Light NV may revise the information and technical data at any time without notice. Version: 29/04/2026

SPL14 - SPY 39 FOCUS 930 DIM5

27328 9305 B

VERVOLLEDIG UW SPECIFICATIE


LED voedingen

armaturen



armaturen geeft aan hoeveel toestellen op de voeding kunnen worden aangesloten (min -> max). De waarden vóór en na de 'I' komen respectievelijk overeen met de minimale en maximale aanstroom. Waarden tussen haakjes zijn van toepassing op 110V.


Min. stroom | Max. stroom



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: niet dimbaar



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: niet dimbaar




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: niet dimbaar

Uitsparingsmaat (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20


Dimtype: niet dimbaar

Uitsparingsmaat (mm): 40


COMPATIBELE DRAAGSTRUCTUREN

SPLITLINE 14 profile

Beschikbare kleuren



27300 0020 SPL14 - PROFILE 2m



27300 0030 SPL14 - PROFILE 3m



Notes:

DELTALIGHT

SPL14 - SPY 39 FOCUS 930 DIM5

27328 9305 B