DELTALIGHT




DOT.COM L2 ST 93032

REFERENCE 424 213 02 932 W-C

AVAILABLE IN
BLACK-BLACK 424 213 02 932 B-B
BLACK-CHROMED 424 213 02 932 B-C
BLACK-FLEMISH GOLD 424 213 02 932 B-FG
WHITE-BLACK 424 213 02 932 W-B
WHITE-CHROMED 424 213 02 932 W-C
WHITE-FLEMISH GOLD 424 213 02 932 W-FG





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 84 x 40
RECESSED DEPTH (MM)	62
THICKNESS OF MOUNTING SURFACE (MM)	max.30
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	2 x REFLECTOR FL-32° EXCL.LED POWER SUPPLY 500-1050mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 2,8-6,3W / CRI>90 (R9: 50) / 3000K / 324-613lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
BEAMANGLE	32°
LED TECHNICS (LIGHT SOURCE)	613lm // 6,3W // 97lm/W
LED TECHNICS (LUMINAIRE)	455lm // 7,2W // 63lm/W

Requirements

LED POWER SUPPLY 500 / 1050mA-DC DIM

For detailed installation instructions, please consult the manual : **424_213_02_XXX_HAND.pdf**

DELTALIGHT

DOT.COM L2 ST 93032

424 213 02 932 W-C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 — 7

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 7

Dimtype: DALI


Cutout dimension (mm): 45



300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL — 7

Dimtype: non-dimmable

Cutout dimension (mm): 30



300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL — 7


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

DELTALIGHT

DOT.COM L2 ST 93032


424 213 02 932 W-C



300 48 700 ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1 — 7

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 700 ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 — 7

Dimtype: DALI


Cutout dimension (mm): 45



300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL — 7

Dimtype: non-dimmable


Cutout dimension (mm): 30



300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL — 7

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 8 | 7

Dimtype: mains (phase cut-off) or push button


Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 12(12) | 12(9) | 9(6)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 8(5) | 7(3)


Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — 2->7 | 2->7


Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 8(5) | 7(3) | -

Dimtype: DALI

Cutout dimension (mm): 72




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 7(5) | 4(3) | -

Dimtype: 1-10V or push button

Cutout dimension (mm): 55

DOT.COM L2 ST 93032


424 213 02 932 W-C



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 7(5) | 4(3) | -

Dimtype: DALI


Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV 6->14 | 5->14 | 5->11

Dimtype: non-dimmable


Cutout dimension (mm): 90



300 90 136 LED POWER SUPPLY MULTI-POWER HC DIM9 7(6)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 90



300 90 148 LED POWER SUPPLY 1050mA-DC / 22W 3(1)

Dimtype: non-dimmable


Cutout dimension (mm): 48



21012 0010 LED POWER SUPPLY MULTI POWER 2->7 | 2->7 | 2->6

Dimtype: non-dimmable


Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 2->9 | 2->8 | 2->6

Dimtype: 1-10V


Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 2->9 | 2->9 | 2->6

Dimtype: DALI


Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL 12(12) | 12(9) | 9(6)

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 2->9 | 2->8 | 2->6

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 3->4 | 3->4 | -


Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55

DELTALIGHT

DOT.COM L2 ST 93032


424 213 02 932 W-C



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 6->9 | 6->8 | -

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 2->7 | 2->4 | -

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 48



21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 3->3

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 40



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 7

Dimtype: DALI

Cutout dimension (mm): 30



21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 7

Dimtype: DALI

Cutout dimension (mm): 30

Notes: